

View Online at <https://aerobasegroup.com/nsn/5985-01-612-8652>

Body Style:

Rectangular

Overall Length:

2.06 inches

Overall Height:

2.27 inches

Overall Width:

0.56 inches

Frequency Rating:

0.0 gigahertz and 18.0 gigahertz single frequency operating

Unthreaded Mounting Hole Diameter:

0.120 inches

Switch Type:

Transfer

Longest Horizontal Distance Between Mounting Centers:

1.320 inches single mounting facility pattern

Shortest Horizontal Distance Between Mounting Centers:

0.440 inches single mounting facility pattern

End Application:

Global hawk asip

Voltage Standing Wave Ratio:

1.3 3rd

Insertion Loss In Decibels:

0.3 3rd

Coaxial Connector Series Designation:

Sma

Connector End Design:

Female

Minimum Crosstalk Rating In Decibels:

85.0 1st

Actuator Operating Method:

Relay

Actuator Voltage In Volts:

12.0

Switch Operation Sequence:

Breaks before makes

Switching Time:

10.0 milliseconds

Switch Return Mechanism Type:

Fail-safe

Pole Quantity:

2

Throw Quantity:

3

Coupling Position Quantity:

1

Mounting Facility Type And Quantity:

4 unthreaded hole

Mounting Facility Pattern:

Four position in-line single mounting facility pattern

Product Name:

Miniature failsafe 2p3t coaxial switch

Special Features:

50 ohms, operating temp range: -55 to +85 degrees c. Ttl drivers w/diodes, moisture seal

Terminal Type And Quantity:

5 receptacle, coaxial and 2 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A158a0