Radio Frequency Transmission Line Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-615-9924

| · · · · · · · · · · · · · · · · · · · |
|---|
| Body Style: |
| Rectangular |
| Overall Length: |
| 4.0 millimeters |
| Overall Height: |
| 4.0 millimeters |
| Overall Width: |
| 0.9 millimeters |
| Frequency Rating: |
| 0.0 megahertz and 3000.0 megahertz single frequency operating |
| Switch Type: |
| Transfer |
| End Application: |
| 5865-01-567-8646 |
| Insertion Loss In Decibels: |
| 1.4 single |
| Minimum Crosstalk Rating In Decibels: |
| 46.0 2nd |
| Actuator Operating Method: |
| Solid state |
| Actuator Current Type And Rating In Amps: |
| 0.3 dc |
| Actuator Voltage In Volts: |
| 3.0 |
| Switching Time: |
| 2.0 microseconds |
| Pole Quantity: |
| 1 |
| Throw Quantity: |
| 2 |
| Coupling Position Quantity: |
| 2 |
| Mounting Facility Type And Quantity: |
| 1 plug-in |
| Product Name: |
| Spdt rf switch |
| Material: |
| Copper contact (s) |
| Unpackaged Unit Weight: |
| 0.04 grams |
| Terminal Type And Quantity: |
| 20 pin |

Radio Frequency Transmission Line Switch - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A158a0