NSN 5985-01-621-5390

Fixed Attenuator - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5985-01-621-5390

Application Design:

| Application Design: |
|--|
| Transmission line |
| Body Material: |
| Aluminum |
| Body Style: |
| Rectangular terminal/terminals on three surfaces |
| Overall Length: |
| 0.650 inches |
| Overall Height: |
| 0.040 inches |
| Overall Width: |
| 0.375 inches |
| Operating Tempurature Range: |
| -55.0 to 150.0 degrees celsius |
| Voltage Standing Wave Ratio: |
| 1.5 |
| Input Impedance Rating In Ohms: |
| 50.0 |
| Output Impedance Rating In Ohms: |
| 50.0 |
| Power Rating: |
| 1.5 watts average |
| Rf Signal Attenuation In Decibels: |
| 10.0 |
| Terminal Type And Quantity: |
| 3 tab, solder lug |
| Frequency Range: |
| Between 0.0 hertz and 12.4 gigahertz |
| Precious Material And Location: |
| Solderable tabs gold |
| Precious Material: |
| Gold |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Vas - damil/mli |

Fiig:

A20000