

View Online at <https://aerobasegroup.com/nsn/5985-01-655-1278>

Body Style:

Cylindrical w/rectangular base

Overall Length:

3.30 inches

Overall Height:

2.00 inches

Overall Width:

2.00 inches

Frequency Rating:

18.0 gigahertz single frequency operating

Unthreaded Mounting Hole Diameter:

0.13 inches

Switch Type:

Nontransfer

Distance Between Mounting Facility Centers:

1.74 inches single mounting facility pattern

Operating Temperature Range:

-25.0 to 65.0 degrees celsius

End Application:

Test set, guided missile

Voltage Standing Wave Ratio:

1.50 single

Insertion Loss In Decibels:

0.5 single

Minimum Crosstalk Rating In Decibels:

60.0 single

Actuator Operating Method:

Relay

Actuator Current Type And Rating In Amps:

160.0 dc

Actuator Voltage In Volts:

28.0

Switch Operation Sequence:

Breaks before makes

Switching Time:

15.0 milliseconds

Pole Quantity:

6

Mounting Facility Type And Quantity:

4 unthreaded hole

Mounting Facility Pattern:

Four position rectangular single mounting facility pattern

Product Name:

Switch, rf sp6t

Unpackaged Unit Weight:

10.0 ounces

Terminal Type And Quantity:

7 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A158a0