## NSN 5990-00-001-1764

Differential Transmitter Synchro - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5990-00-001-1764 **Body Material:** Aluminum or steel, corrosion resisting **Body Style:** Standard round a **Pilot Diameter:** Between 0.4995 inches and 0.5000 inches **Overall Length:** 1.8800 inches Flange Diameter: 0.7500 inches Flange Thickness: Between 0.0590 inches and 0.0650 inches **Undercut Diameter:** Between 0.6880 inches and 0.6910 inches **Undercut Width:** Between 0.0590 inches and 0.0650 inches **Shaft Diameter:** 0.0895 inches single shaft and 0.0900 inches single shaft **Shaft Length:** 0.3660 inches single shaft and 0.3990 inches single shaft **Maximum Tempurature Rise:** 

12.0 degrees celsius

**Body Size:** 

**Stator Input Voltage Rating In Volts:** 

11.8

**Stator Input Current Rating:** 

87.0 milliamperes

**Stator Input Electrical Power Rating:** 

210.0 milliwatts

Frequency In Hertz:

400.0

**Zro Resistance In Ohms:** 

38.00

**Zso Resistance In Ohms:** 

28.00

**Zrs Impedance Magnitude In Ohms:** 

Between 35.00 and 48.00

Zrs Impedance Angle In Deg:

Between 15.00 and 20.00

**Rotor Dc Resistance In Ohms:** 

36.00

NSN 5990-00-001-1764 Differential Transmitter Synchro - Page 2 of 2



Stator Dc Resistance In Ohms:
24.00
Phase Shift Angle In Deg:
9.500 input to output
Maximum Fundamental Null Voltage In Millivolts Per Volt:
20.00 output
Maximum Total Null Voltage Output In Millivolts Per Volt:
30.00
Electrical Error Angular Range In Minutes:
-7.0/+7.0
Actuator Friction Torque At Minus 55 Deg Celsius:
9.0 centimeter-grams
Actuator Friction Torque At Plus 25 Deg Celsius:
4.0 centimeter-grams
Pilot Length:
Between 0.0380 inches and 0.0430 inches
Mounting Surface To Terminal End Distance:
1.3000 inches
Terminal Location:
Rear
Plus J Zro Reactance In Ohms:
122.00
Shaft Slot Depth:
0.0250 inches single shaft and 0.0350 inches single shaft
Plus J Zso Reactance In Ohms:
114.00
Shaft Slot Width:
0.0200 inches single shaft and 0.0300 inches single shaft
Shaft Type:
Round, slotted single shaft
Transformation Ratio:
1.127 rotor to stator
Terminal Type And Quantity:
6 turret
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A07800