

View Online at <https://aerobasegroup.com/nsn/5990-00-001-4570>

**Body Material:**

Any acceptable

**Body Style:**

Standard round a

**Pilot Diameter:**

Between 0.4995 inches and 0.5000 inches

**Overall Length:**

1.6350 inches

**Flange Diameter:**

Between 0.7470 inches and 0.7500 inches

**Flange Thickness:**

0.0620 inches

**Undercut Diameter:**

Between 0.6880 inches and 0.6910 inches

**Undercut Width:**

0.0620 inches

**Shaft Diameter:**

0.0895 inches single shaft and 0.9000 inches single shaft

**Shaft Length:**

0.3600 inches single shaft and 0.3900 inches single shaft

**Fragility Factor:**

Moderately rugged

**Body Size:**

8

**Rotor Input Voltage Rating In Volts:**

115.0

**Frequency In Hertz:**

400.0

**Rotor Input Current Rating:**

30.0 milliamperes

**Rotor Input Electrical Power Rating:**

800.0 milliwatts

**Zro Resistance In Ohms:**

900.00

**Zso Resistance In Ohms:**

20.00

**Zrs Resistance In Ohms:**

1500.00

**Rotor Dc Resistance In Ohms:**

700.00

**Stator Dc Resistance In Ohms:**

10.00

**Phase Shift Angle In Deg:**

11.000 input to output

**Torque Gradient Per Angular Deg:**

2400.000 millimeter-milligrams

**Pilot Length:**

0.0430 inches

**Mounting Surface To Terminal End Distance:**

1.0815 inches

**Terminal Location:**

Rear

**Plus J Zro Reactance In Ohms:**

3850.00

**Shaft Slot Depth:**

0.0200 inches single shaft

**Plus J Zso Reactance In Ohms:**

36.00

**Shaft Slot Width:**

0.0200 inches single shaft

**Plus J Zrs Reactance In Ohms:**

375.00

**Shaft Type:**

Round, slotted single shaft

**Terminal Type And Quantity:**

5 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A07800