

View Online at <https://aerobasegroup.com/nsn/5990-00-018-9719>

Body Material:

Steel, stainless

Body Style:

Standard round c

Shoulder Diameter:

Between 1.5615 inches and 1.5620 inches

Pilot Diameter:

Between 0.9370 inches and 0.9375 inches

Overall Length:

3.2100 inches

Flange Diameter:

Between 1.7450 inches and 1.7500 inches

Flange Thickness:

0.0930 inches

Undercut Diameter:

1.6250 inches

Undercut Width:

0.0780 inches

Shaft Diameter:

0.1870 inches single shaft and 0.1872 inches single shaft

Shaft Length:

0.5400 inches single shaft

Maximum Temperature Rise:

20.0 degrees celsius

Body Size:

18

Stator Input Voltage Rating In Volts:

90.0

Stator Input Current Rating:

128.0 milliamperes

Stator Input Electrical Power Rating:

950.0 milliwatts

Frequency In Hertz:

400.0

Zso Impedance Magnitude In Ohms:

Between 610.00 and 785.00

Zso Impedance Angle In Deg:

Between 83.00 and 86.50

Zrs Impedance Magnitude In Ohms:

Between 76.00 and 110.00

Zrs Impedance Angle In Deg:

Between 40.00 and 55.00

Phase Shift Angle In Deg:

2.000 input to output

Maximum Fundamental Null Voltage In Millivolts Per Volt:

40.00 output

Maximum Total Null Voltage Output In Millivolts Per Volt:

75.00

Electrical Error Angular Range In Minutes:

-6.0 to 6.0

Spline Tooth Quantity:

21 single shaft

Torque Gradient Per Angular Deg:

0.100 inch-ounces

Alignment Hole Quantity:

4

Pilot Length:

0.0400 inches

Shoulder Length:

0.1320 inches

Mounting Surface To Terminal End Distance:

2.6700 inches

Spline Tooth Diametral Pitch:

120 single shaft

Shaft Thread Series Designator:

Unf single shaft

Shaft Thread Direction:

Right-hand single shaft

Shaft Thread Class:

2a

Terminal Location:

Rear

Shaft Thread Length:

0.2000 inches single shaft

Shaft Type:

Round, slotted single shaft

Alignment Hole Depth:

0.1250 inches

Transformation Ratio:

1.154 rotor to stator

Alignment Hole Bolt Circle Diameter:

1.2500 inches

Shaft Thread Size:

0.190 inches single shaft

Test Data Document:

81349-mil-s-20708 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

Terminal Type And Quantity:

5 screw

Specification Data:

81349-mil-s-20708/30 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A07800