

View Online at https://aerobasegroup.com/nsn/5990-00-018-9720

····· ································
Body Material:
Steel, stainless
Body Style:
Standard round d
Shoulder Diameter:
Between 1.9850 inches and 1.9900 inches
Pilot Diameter:
0.5950 inches
Second Shoulder Diameter:
Between 1.9985 inches and 1.9995 inches
Second Shoulder Length:
0.1700 inches
Overall Length:
4.5490 inches
Flange Diameter:
Between 2.2490 inches and 2.2500 inches
Flange Thickness:
0.2500 inches
Body Diameter:
1.9900 inches
Shaft Diameter:
0.2403 inches single shaft and 0.2405 inches single shaft
Shaft Length:
0.7190 inches single shaft
Maximum Tempurature Rise:
25.0 degrees celsius
Body Size:
23
Stator Input Voltage Rating In Volts:
90.0
Stator Input Current Rating:
866.0 milliamperes
Stator Input Electrical Power Rating:
7.0 milliwatts
Frequency In Hertz:
400.0
Zro Impedance Angle In Deg:
Between 47.00 and 53.00
Zso Impedance Magnitude In Ohms:
Between 90.00 and 112.00
Zso Impedance Angle In Deg:
84.00



**Zrs Impedance Magnitude In Ohms:** Between 11.00 and 15.00 Zrs Impedance Angle In Deg: Between 47.00 and 53.00 Phase Shift Angle In Deg: 2.000 input to output **Electrical Error Angular Range In Minutes:** -8.0/+8.0 Spline Tooth Quantity: 22 single shaft Actuator Friction Torque At Plus 25 Deg Celsius: 0.20 inch-ounces **Torque Gradient Per Angular Deg:** 0.160 inch-ounces **Pilot Length:** 0.0430 inches Shoulder Length: 0.2500 inches Aft Of First Flange Diameter: Between 1.9985 inches and 1.9995 inches **Mounting Surface To Terminal End Distance:** 3.8300 inches **Spline Tooth Diametral Pitch:** 96 single shaft Shaft Thread Series Designator: Unf single shaft **Shaft Thread Direction:** Right-hand single shaft Shaft Thread Class: 2a single shaft **Terminal Location:** Rear Shaft Thread Length: 0.2900 inches single shaft Shaft Type: Spline w/threads single shaft Transformation Ratio: 1.154 rotor to stator Shaft Thread Size: 0.250 inches single shaft **Test Data Document:** 

81349-mil-s-20708 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:** 



## **Specification Data:**

81349-mil-s-20708/48 government specification

Shelf Life:

N/a

Unit Of Measure:

---

## Demilitarization:

Yes - demil/mli

Fiig:

A07800