Control Transformer Synchro - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5990-00-052-3143

view Online at https://aerobasegroup.com/nsi//3550-00-052-5145
Body Material:
Steel, corrosion resisting
Body Style:
Standard round a
Pilot Diameter:
Between 0.4995 inches and 0.5000 inches
Overall Length:
1.7410 inches
Flange Diameter:
Between 0.7490 inches and 0.7500 inches
Flange Thickness:
0.0620 inches
Undercut Diameter:
Between 0.6880 inches and 0.6910 inches
Undercut Width:
0.0620 inches
Shaft Diameter:
0.0895 inches single shaft and 0.0900 inches single shaft
Shaft Length:
0.5000 inches single shaft
Fragility Factor:
Moderately rugged
Body Size:
8
Stator Input Voltage Rating In Volts:
11.8
Stator Input Current Rating:
30.0 milliamperes
Stator Input Electrical Power Rating:
73.0 milliwatts
Frequency In Hertz:
400.0
Zro Resistance In Ohms:
470.00
Zso Resistance In Ohms:
81.00
Rotor Dc Resistance In Ohms:
64.00
Stator Dc Resistance In Ohms:
365.00
Phase Shift Angle In Deg:
8.500 input to output

NSN 5990-00-052-3143

Control Transformer Synchro - Page 2 of 2



Electrical Error Angular Range In Minutes: -7.0/+7.0 Actuator Friction Torque At Minus 55 Deg Celsius: 9.00 centimeter-grams Actuator Friction Torque At Plus 25 Deg Celsius: 3.00 centimeter-grams **Pilot Length:** 0.0430 inches Mounting Surface To Terminal End Distance: 1.2410 inches **Terminal Location:** Rear Plus J Zro Reactance In Ohms: 1770.00 Shaft Slot Depth: 0.0250 inches single shaft Plus J Zso Reactance In Ohms: 330.00 Shaft Slot Width: 0.0200 inches single shaft Shaft Type: Round, slotted single shaft **Terminal Type And Quantity:** 5 wire lead Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A07800