

View Online at <https://aerobasegroup.com/nsn/5990-00-055-1956>

Body Material:

Steel, stainless

Body Style:

Standard round a

Pilot Diameter:

0.5000 inches

Overall Length:

1.5960 inches

Flange Diameter:

0.7550 inches

Flange Thickness:

0.0620 inches

Undercut Diameter:

0.6910 inches

Undercut Width:

0.0620 inches

Shaft Diameter:

0.0900 inches single shaft

Shaft Length:

0.3320 inches single shaft

Fragility Factor:

Moderately rugged

Body Size:

8

Stator Input Voltage Rating In Volts:

26.0

Stator Input Current Rating:

22.0 milliamperes

Stator Input Electrical Power Rating:

58.0 milliwatts

Frequency In Hertz:

400.0

Zro Resistance In Ohms:

800.00

Zso Resistance In Ohms:

120.00

Zrs Resistance In Ohms:

872.00

Rotor Dc Resistance In Ohms:

550.00

Stator Dc Resistance In Ohms:

100.00

Phase Shift Angle In Deg:

9.000 input to output

Maximum Total Null Voltage Output In Millivolts Per Volt:

0.03

Actuator Friction Torque At Minus 55 Deg Celsius:

6.00 centimeter-grams

Actuator Friction Torque At Plus 25 Deg Celsius:

3.00 centimeter-grams

Shaft Maximum Radial Play:

0.0005 inches

Shaft End Play:

Between 0.0003 inches and 0.0008 inches

Pilot Length:

0.0400 inches

Mounting Surface To Terminal End Distance:

1.2400 inches

Shaft Maximum Runout:

0.0010 inches

Terminal Location:

Rear

Plus J Zro Reactance In Ohms:

2500.00

Shaft Slot Depth:

0.0250 inches single shaft

Plus J Zso Reactance In Ohms:

450.00

Shaft Slot Width:

0.0200 inches single shaft

Plus J Zrs Reactance In Ohms:

245.00

Shaft Type:

Round, slotted single shaft

Transformation Ratio:

2.208 rotor to stator

Terminal Type And Quantity:

5 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A07800