

View Online at <https://aerobasegroup.com/nsn/5990-00-060-1667>

Body Material:

Any acceptable

Body Style:

Standard round c

Shoulder Diameter:

Between 0.9995 inches and 1.0000 inches

Pilot Diameter:

Between 0.6245 inches and 0.6250 inches

Overall Length:

2.3350 inches

Flange Diameter:

Between 1.0610 inches and 1.0620 inches

Flange Thickness:

0.0930 inches

Undercut Diameter:

0.9750 inches

Undercut Width:

0.0500 inches

Shaft Diameter:

0.1195 inches single shaft and 0.1200 inches single shaft

Shaft Length:

0.3600 inches single shaft and 0.3900 inches single shaft

Fragility Factor:

Moderately rugged

Body Size:

11

Rotor Input Voltage Rating In Volts:

26.0

Frequency In Hertz:

400.0

Rotor Input Current Rating:

90.0 milliamperes

Rotor Input Electrical Power Rating:

400.0 milliwatts

Pilot Length:

Between 0.0500 inches and 0.0590 inches

Shoulder Length:

Between 0.0590 inches and 0.0650 inches

Mounting Surface To Terminal End Distance:

1.8350 inches

Terminal Location:

Rear

Shaft Slot Depth:

0.0220 inches single shaft and 0.0320 inches single shaft

Shaft Slot Width:

0.0220 inches single shaft and 0.0320 inches single shaft

Shaft Type:

Round, slotted single shaft

Transformation Ratio:

0.454 rotor to stator

Terminal Type And Quantity:

5 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A07800