

View Online at <https://aerobasegroup.com/nsn/5990-00-060-2576>

**Body Material:**

Steel, corrosion resisting

**Body Style:**

Standard round c

**Shoulder Diameter:**

0.9750 inches

**Pilot Diameter:**

0.6250 inches

**Overall Length:**

1.9360 inches

**Flange Diameter:**

1.0620 inches

**Flange Thickness:**

0.0930 inches

**Undercut Diameter:**

1.0000 inches

**Undercut Width:**

0.0500 inches

**Shaft Diameter:**

0.1200 inches single shaft

**Shaft Length:**

0.4360 inches single shaft

**Fragility Factor:**

Moderately rugged

**Body Size:**

11

**Rotor Input Voltage Rating In Volts:**

115.0

**Frequency In Hertz:**

400.0

**Rotor Input Current Rating:**

70.0 milliamperes

**Rotor Input Electrical Power Rating:**

30.0 milliwatts

**Rotor Dc Resistance In Ohms:**

175.00

**Stator Dc Resistance In Ohms:**

3.20

**Phase Shift Angle In Deg:**

5.600 input to output

**Maximum Fundamental Null Voltage In Millivolts Per Volt:**

17.00 input

**Maximum Total Null Voltage Output In Millivolts Per Volt:**

26.00

**Actuator Friction Torque At Minus 55 Deg Celsius:**

16.0 centimeter-grams

**Actuator Friction Torque At Plus 25 Deg Celsius:**

4.0 centimeter-grams

**Pilot Length:**

0.0620 inches

**Shoulder Length:**

0.0620 inches

**Mounting Surface To Terminal End Distance:**

1.7750 inches

**Terminal Location:**

Rear

**Shaft Slot Depth:**

0.0300 inches single shaft

**Shaft Slot Width:**

0.0250 inches single shaft

**Shaft Type:**

Round, slotted single shaft

**Transformation Ratio:**

0.103 rotor to stator

**Terminal Type And Quantity:**

5 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A07800