Control Transformer Synchro - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5990-00-060-2918

| ····· |
|---|
| Body Material: |
| Steel, stainless |
| Body Style: |
| Standard round a |
| Pilot Diameter: |
| Between 0.4995 inches and 0.5000 inches |
| Overall Length: |
| Between 1.7010 inches and 1.7250 inches |
| Flange Diameter: |
| Between 0.7530 inches and 0.7550 inches |
| Flange Thickness: |
| 0.0620 inches |
| Undercut Diameter: |
| Between 0.6870 inches and 0.6920 inches |
| Undercut Width: |
| 0.0620 inches |
| Shaft Diameter: |
| 0.1195 inches single shaft and 0.1200 inches single shaft |
| Shaft Length: |
| 0.4610 inches single shaft and 0.4850 inches single shaft |
| Body Size: |
| 8 |
| Stator Input Voltage Rating In Volts: |
| 11.8 |
| Stator Input Current Rating: |
| 30.0 milliamperes |
| Stator Input Electrical Power Rating: |
| 100.0 milliwatts |
| Frequency In Hertz: |
| 400.0 |
| Zro Resistance In Ohms: |
| 645.00 |
| Zso Resistance In Ohms: |
| 110.00 |
| Zrs Resistance In Ohms: |
| 930.00 |
| Rotor Dc Resistance In Ohms: |
| 420.00 |
| Stator Dc Resistance In Ohms: |
| 105.00 |
| Phase Shift Angle In Deg: |
| 10.000 input to output |



Maximum Fundamental Null Voltage In Millivolts Per Volt: 30.00 output Maximum Total Null Voltage Output In Millivolts Per Volt: 40.00 **Electrical Error Angular Range In Minutes:** -10.0 to 10.0 Actuator Friction Torque At Plus 25 Deg Celsius: 3.00 centimeter-grams **Pilot Length:** 0.0400 inches Mounting Surface To Terminal End Distance: 1.2400 inches **Terminal Location:** Rear **Plus J Zro Reactance In Ohms:** 2400.00 Shaft Slot Depth: 0.0300 inches single shaft Plus J Zso Reactance In Ohms: 415.00 Shaft Slot Width: 0.0250 inches single shaft Plus J Zrs Reactance In Ohms: 415.00 Shaft Type: Round, slotted single shaft **Transformation Ratio:** 2.203 rotor to stator **Terminal Type And Quantity:** 5 wire lead Shelf Life: N/a Unit Of Measure: --**Demilitarization:** Yes - demil/mli Fiig: A07800