

View Online at <https://aerobasegroup.com/nsn/5990-00-060-3062>

Body Material:

Steel, corrosion resisting

Body Style:

Standard round b

Shoulder Diameter:

Between 0.9995 inches and 1.0000 inches

Pilot Diameter:

Between 0.4995 inches and 0.5000 inches

Overall Length:

Between 1.9745 inches and 1.9750 inches

Flange Diameter:

Between 1.0610 inches and 1.0620 inches

Flange Thickness:

0.0620 inches

Undercut Width:

0.0810 inches

Shaft Diameter:

0.1195 inches single shaft and 0.1200 inches single shaft

Shaft Length:

0.3750 inches single shaft

Body Size:

11

Stator Input Voltage Rating In Volts:

11.8

Stator Input Current Rating:

138.0 milliamperes

Stator Input Electrical Power Rating:

290.0 milliwatts

Frequency In Hertz:

400.0

Zro Resistance In Ohms:

94.00

Zso Resistance In Ohms:

15.00

Zrs Resistance In Ohms:

81.00

Rotor Dc Resistance In Ohms:

45.00

Stator Dc Resistance In Ohms:

8.50

Phase Shift Angle In Deg:

5.000 input to output

Maximum Total Null Voltage Output In Millivolts Per Volt:

30.00

Electrical Error Angular Range In Minutes:

-12.0/+12.0

Actuator Friction Torque At Minus 55 Deg Celsius:

6.0 centimeter-grams

Actuator Friction Torque At Plus 25 Deg Celsius:

3.0 centimeter-grams

Pilot Length:

0.0620 inches

Shoulder Length:

0.0620 inches

Mounting Surface To Terminal End Distance:

1.5370 inches

Distance From Shaft Hole Center To End:

1.5380 inches single shaft

Terminal Location:

Rear

Plus J Zro Reactance In Ohms:

436.00

Shaft Slot Depth:

0.0220 inches single shaft and 0.0320 inches single shaft

Plus J Zso Reactance In Ohms:

72.00

Shaft Slot Width:

0.0220 inches single shaft and 0.0320 inches single shaft

Plus J Zrs Reactance In Ohms:

40.00

Shaft Type:

Round, slotted single shaft

Terminal Type And Quantity:

5 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A07800