

View Online at <https://aerobasegroup.com/nsn/5990-00-061-3360>

Body Material:

Steel, corrosion resisting

Body Style:

Standard round a

Pilot Diameter:

Between 0.4995 inches and 0.5000 inches

Overall Length:

1.5750 inches

Flange Diameter:

Between 0.7450 inches and 0.7500 inches

Flange Thickness:

0.0620 inches

Undercut Diameter:

Between 0.6880 inches and 0.6910 inches

Undercut Width:

0.0620 inches

Shaft Diameter:

0.0895 inches single shaft and 0.0900 inches single shaft

Shaft Length:

0.3750 inches single shaft

Body Size:

8

Rotor Input Voltage Rating In Volts:

26.0

Frequency In Hertz:

400.0

Rotor Input Current Rating:

120.0 milliamperes

Rotor Input Electrical Power Rating:

600.0 milliwatts

Zro Resistance In Ohms:

39.00

Zso Resistance In Ohms:

11.00

Zrs Resistance In Ohms:

76.00

Rotor Dc Resistance In Ohms:

29.40

Stator Dc Resistance In Ohms:

11.50

Phase Shift Angle In Deg:

7.500 input to output

Electrical Error Angular Range In Minutes:

-7.0 to 7.0

Torque Gradient Per Angular Deg:

2000.0 millimeter-milligrams

Pilot Length:

0.0400 inches

Mounting Surface To Terminal End Distance:

1.2400 inches

Terminal Location:

Rear

Plus J Zro Reactance In Ohms:

225.00

Shaft Slot Depth:

0.0260 inches single shaft

Plus J Zso Reactance In Ohms:

39.00

Shaft Slot Width:

0.0250 inches single shaft

Plus J Zrs Reactance In Ohms:

24.00

Shaft Type:

Round, slotted single shaft

Terminal Type And Quantity:

5 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A07800