

View Online at <https://aerobasegroup.com/nsn/5990-00-070-8325>

Body Material:

Steel, corrosion resisting

Body Style:

Standard round c

Shoulder Diameter:

0.8123 inches

Pilot Diameter:

0.5000 inches

Overall Length:

1.5490 inches

Flange Diameter:

0.9370 inches

Flange Thickness:

0.0620 inches

Undercut Diameter:

0.8400 inches

Undercut Width:

0.0620 inches

Shaft Diameter:

0.0900 inches single shaft

Shaft Length:

0.2700 inches single shaft

Body Size:

10

Rotor Input Voltage Rating In Volts:

115.0

Frequency In Hertz:

400.0

Rotor Input Current Rating:

37.0 milliamperes

Rotor Input Electrical Power Rating:

94.0 milliwatts

Zro Resistance In Ohms:

725.00

Zso Resistance In Ohms:

7.65

Zrs Resistance In Ohms:

1050.00

Rotor Dc Resistance In Ohms:

450.00

Stator Dc Resistance In Ohms:

3410.00

Phase Shift Angle In Deg:

8.500 input to output

Maximum Fundamental Null Voltage In Millivolts Per Volt:

30.00 input

Maximum Total Null Voltage Output In Millivolts Per Volt:

30.00

Electrical Error Angular Range In Minutes:

-7.0/+7.0

Actuator Friction Torque At Minus 55 Deg Celsius:

6.0 centimeter-grams

Actuator Friction Torque At Plus 25 Deg Celsius:

3.0 centimeter-grams

Pilot Length:

0.0380 inches

Shoulder Length:

0.0620 inches

Mounting Surface To Terminal End Distance:

1.2790 inches

Terminal Location:

Rear

Plus J Zro Reactance In Ohms:

3410.00

Shaft Slot Depth:

0.0350 inches single shaft

Plus J Zso Reactance In Ohms:

30.55

Shaft Slot Width:

0.0250 inches single shaft

Plus J Zrs Reactance In Ohms:

325.00

Shaft Type:

Round, slotted single shaft

Transformation Ratio:

0.103 rotor to stator

Terminal Type And Quantity:

5 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A07800