

View Online at <https://aerobasegroup.com/nsn/5990-00-072-9408>

Body Material:

Steel, corrosion resisting

Body Style:

Standard round b

Shoulder Diameter:

Between 0.9995 inches and 1.0000 inches

Pilot Diameter:

Between 0.6245 inches and 0.6250 inches

Overall Length:

Between 2.3220 inches and 2.3270 inches

Flange Diameter:

Between 1.0580 inches and 1.0650 inches

Flange Thickness:

0.0930 inches

Undercut Width:

0.0500 inches

Shaft Diameter:

0.1195 inches single shaft and 0.1200 inches single shaft

Shaft Length:

0.6140 inches single shaft and 0.6380 inches single shaft

Fragility Factor:

Moderately rugged

Maximum Temperature Rise:

2.5 degrees celsius

Body Size:

11

Rotor Input Voltage Rating In Volts:

26.0

Frequency In Hertz:

400.0

Rotor Input Current Rating:

52.0 milliamperes

Rotor Input Electrical Power Rating:

340.0 milliwatts

Zro Impedance Magnitude In Ohms:

550.00

Zro Impedance Angle In Deg:

78.10

Rotor Dc Resistance In Ohms:

75.00

Stator Dc Resistance In Ohms:

15.50

Transformation Ratio Equality In Percent:

0.4

Phase Shift Angle In Deg:

8.000 input to output

Maximum Fundamental Null Voltage In Millivolts Per Volt:

18.00 output

Maximum Total Null Voltage Output In Millivolts Per Volt:

30.00

Actuator Friction Torque At Minus 55 Deg Celsius:

16.00 centimeter-grams

Actuator Friction Torque At Plus 25 Deg Celsius:

4.00 centimeter-grams

Pilot Length:

0.0620 inches

Shoulder Length:

0.0620 inches

Mounting Surface To Terminal End Distance:

Between 1.6980 inches and 1.7030 inches

Terminal Location:

Rear

Shaft Slot Depth:

0.0300 inches single shaft

Shaft Slot Width:

0.0250 inches single shaft

Shaft Type:

Round, slotted single shaft

Transformation Ratio:

0.484 rotor to stator

Terminal Type And Quantity:

7 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A07800