

View Online at <https://aerobasegroup.com/nsn/5990-00-105-7096>

Body Material:

Steel, stainless

Body Style:

Standard round c

Shoulder Diameter:

Between 0.9995 inches and 1.0000 inches

Pilot Diameter:

Between 0.6245 inches and 0.6250 inches

Overall Length:

Between 4.5350 inches and 4.5650 inches

Flange Diameter:

1.0620 inches

Flange Thickness:

0.0930 inches

Undercut Diameter:

0.9850 inches

Undercut Width:

0.0450 inches

Shaft Diameter:

0.1195 inches single shaft and 0.1200 inches single shaft

Shaft Length:

0.5230 inches single shaft and 0.5530 inches single shaft

Body Size:

13

Rotor Input Voltage Rating In Volts:

26.0

Frequency In Hertz:

400.0

Rotor Input Current Rating:

280.0 milliamperes

Rotor Input Electrical Power Rating:

1.11 watts

Zro Resistance In Ohms:

16.00

Zso Resistance In Ohms:

3.70

Zss Resistance In Ohms:

22.00

Rotor Dc Resistance In Ohms:

9.00

Stator Dc Resistance In Ohms:

3.00

Phase Shift Angle In Deg:

8.000 input to output

Maximum Fundamental Null Voltage In Millivolts Per Volt:

17.00 output

Maximum Total Null Voltage Output In Millivolts Per Volt:

26.00

Pilot Length:

0.0620 inches

Shoulder Length:

0.0620 inches

Mounting Surface To Terminal End Distance:

4.0120 inches

Terminal Location:

Side

Plus J Zro Reactance In Ohms:

107.00

Shaft Slot Depth:

0.0200 inches single shaft and 0.0350 inches single shaft

Plus J Zso Reactance In Ohms:

18.10

Shaft Slot Width:

0.0200 inches single shaft and 0.0350 inches single shaft

Shaft Type:

Round, slotted single shaft

Plus J Zss Reactance In Ohms:

8.90

Transformation Ratio:

0.454 rotor to stator

Terminal Type And Quantity:

5 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A07800