

View Online at <https://aerobasegroup.com/nsn/5990-00-121-2134>

Body Material:

Steel, corrosion resisting

Body Style:

Standard round a

Pilot Diameter:

0.5000 inches

Overall Length:

1.5880 inches

Flange Diameter:

0.7500 inches

Flange Thickness:

0.0620 inches

Undercut Diameter:

0.6910 inches

Undercut Width:

0.0620 inches

Shaft Diameter:

0.0900 inches single shaft

Shaft Length:

0.3750 inches single shaft

Fragility Factor:

Moderately rugged

Body Size:

8

Stator Input Voltage Rating In Volts:

26.0

Stator Input Current Rating:

81.0 milliamperes

Stator Input Electrical Power Rating:

200.0 milliwatts

Frequency In Hertz:

400.0

Zro Resistance In Ohms:

250.00

Zso Resistance In Ohms:

35.00

Zrs Resistance In Ohms:

325.00

Rotor Dc Resistance In Ohms:

225.00

Stator Dc Resistance In Ohms:

25.00

Phase Shift Angle In Deg:

4.000 input to output

Maximum Fundamental Null Voltage In Millivolts Per Volt:

30.00 input

Maximum Total Null Voltage Output In Millivolts Per Volt:

70.00

Electrical Error Angular Range In Minutes:

-7.0/+7.0

Actuator Friction Torque At Minus 55 Deg Celsius:

6.0 centimeter-grams

Actuator Friction Torque At Plus 25 Deg Celsius:

3.0 centimeter-grams

Shaft Maximum Radial Play:

0.0006 inches

Pilot Length:

0.0430 inches

Mounting Surface To Terminal End Distance:

1.2410 inches

Terminal Location:

Rear

Plus J Zro Reactance In Ohms:

625.00

Shaft Slot Depth:

0.0250 inches single shaft

Plus J Zso Reactance In Ohms:

140.00

Shaft Slot Width:

0.0200 inches single shaft

Plus J Zrs Reactance In Ohms:

65.00

Shaft Type:

Round, slotted single shaft

Transformation Ratio:

0.465 rotor to stator

Terminal Type And Quantity:

5 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A07800