

View Online at <https://aerobasegroup.com/nsn/5990-00-136-8030>

**Body Material:**

Steel, stainless

**Body Style:**

Standard round c

**Shoulder Diameter:**

Between 0.9995 inches and 1.0000 inches

**Pilot Diameter:**

Between 0.6245 inches and 0.6250 inches

**Overall Length:**

Between 4.2600 inches and 4.2900 inches

**Flange Diameter:**

1.0620 inches

**Flange Thickness:**

0.0930 inches

**Undercut Diameter:**

0.9750 inches

**Undercut Width:**

0.0500 inches

**Shaft Diameter:**

0.1195 inches single shaft and 0.1200 inches single shaft

**Shaft Length:**

0.3600 inches single shaft and 0.3900 inches single shaft

**Body Size:**

11

**Stator Input Voltage Rating In Volts:**

11.8

**Stator Input Current Rating:**

260.0 milliamperes

**Stator Input Electrical Power Rating:**

570.0 milliwatts

**Frequency In Hertz:**

400.0

**Zro Resistance In Ohms:**

18.00

**Zso Resistance In Ohms:**

8.40

**Zrs Resistance In Ohms:**

18.00

**Rotor Dc Resistance In Ohms:**

14.50

**Stator Dc Resistance In Ohms:**

6.20

**Phase Shift Angle In Deg:**

7.000 input to output

**Maximum Total Null Voltage Output In Millivolts Per Volt:**

30.00

**Electrical Error Angular Range In Minutes:**

-7.0 to 7.0

**Actuator Friction Torque At Minus 55 Deg Celsius:**

16.00 centimeter-grams

**Actuator Friction Torque At Plus 25 Deg Celsius:**

4.00 centimeter-grams

**Pilot Length:**

Between 0.0590 inches and 0.0650 inches

**Shoulder Length:**

Between 0.0590 inches and 0.0650 inches

**Mounting Surface To Terminal End Distance:**

3.9000 inches

**Terminal Location:**

Rear

**Plus J Zro Reactance In Ohms:**

70.00

**Shaft Slot Depth:**

0.0220 inches single shaft and 0.0320 inches single shaft

**Plus J Zso Reactance In Ohms:**

38.00

**Shaft Slot Width:**

0.0220 inches single shaft and 0.0320 inches single shaft

**Plus J Zrs Reactance In Ohms:**

7.00

**Shaft Type:**

Round, slotted single shaft

**Terminal Type And Quantity:**

5 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A07800