Control Transformer Synchro - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5990-00-139-2828

Body Material:
Steel, stainless
Body Style:
Standard round b
Shoulder Diameter:
Between 0.8118 inches and 0.8123 inches
Pilot Diameter:
Between 0.4995 inches and 0.5000 inches
Overall Length:
1.6780 inches
Flange Diameter:
Between 0.9369 inches and 0.9370 inches
Flange Thickness:
0.0630 inches
Undercut Width:
0.0620 inches
Shaft Diameter:
0.0895 inches single shaft and 0.0900 inches single shaft
Shaft Length:
0.4370 inches single shaft
Fragility Factor:
Moderately rugged
Body Size:
10
Stator Input Voltage Rating In Volts:
11.8
Stator Input Current Rating:
21.0 milliamperes
Stator Input Electrical Power Rating:
50.0 milliwatts
Frequency In Hertz:
400.0
Zro Resistance In Ohms:
800.00
Zso Resistance In Ohms:
115.00
Rotor Dc Resistance In Ohms:
560.00
Stator Dc Resistance In Ohms:
100.00
Phase Shift Angle In Deg:
10.800 input to output



Electrical Error Angular Range In Minutes:

-10.0/+10.0

**Pilot Length:** 

0.0380 inches

Shoulder Length:

0.0620 inches

Mounting Surface To Terminal End Distance:

1.1790 inches

**Terminal Location:** 

Rear

Plus J Zro Reactance In Ohms:

2900.00

Plus J Zso Reactance In Ohms:

70.00

Shaft Type:

Round single shaft

**Terminal Type And Quantity:** 

5 wire lead

Shelf Life:

N/a

---

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A07800