

View Online at <https://aerobasegroup.com/nsn/5990-00-147-3144>

Body Material:

Steel, corrosion resisting

Body Style:

Standard round a

Pilot Diameter:

Between 0.4995 inches and 0.5000 inches

Overall Length:

1.4050 inches

Flange Diameter:

Between 0.7490 inches and 0.7500 inches

Flange Thickness:

0.0620 inches

Undercut Diameter:

Between 0.6880 inches and 0.6910 inches

Undercut Width:

0.0620 inches

Shaft Diameter:

0.8950 inches single shaft and 0.9000 inches single shaft

Shaft Length:

0.3170 inches single shaft and 0.3470 inches single shaft

Body Size:

8

Stator Input Voltage Rating In Volts:

11.8

Stator Input Current Rating:

11.3 milliamperes

Stator Input Electrical Power Rating:

29.5 milliwatts

Frequency In Hertz:

400.0

Zso Resistance In Ohms:

230.00

Stator Dc Resistance In Ohms:

200.00

Phase Shift Angle In Deg:

9.000 input to output

Electrical Error Angular Range In Minutes:

-7.0/+7.0

Actuator Friction Torque At Minus 55 Deg Celsius:

9.0 centimeter-grams

Actuator Friction Torque At Plus 25 Deg Celsius:

3.0 centimeter-grams

Pilot Length:

0.0430 inches

Mounting Surface To Terminal End Distance:

1.0150 inches

Terminal Location:

Rear

Shaft Slot Depth:

0.0250 inches single shaft

Plus J Zso Reactance In Ohms:

870.00

Shaft Slot Width:

0.0200 inches single shaft

Shaft Type:

Round, slotted single shaft

Transformation Ratio:

0.524 rotor to stator

Terminal Type And Quantity:

5 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A07800