NSN 5990-00-160-1072



Control Transformer Synchro - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5990-00-160-1072 **Body Material:** Steel, corrosion resisting **Body Style:** Standard round a **Pilot Diameter:** Between 0.4995 inches and 0.5000 inches **Overall Length:** 1.7460 inches Flange Diameter: Between 0.7490 inches and 0.7500 inches Flange Thickness: Between 0.0570 inches and 0.0670 inches **Undercut Diameter:** Between 0.6880 inches and 0.6910 inches **Undercut Width:** Between 0.0570 inches and 0.0670 inches **Shaft Diameter:** 0.0895 inches single shaft and 0.0900 inches single shaft **Shaft Length:** 0.4570 inches single shaft **Fragility Factor:** Moderately rugged **Body Size: Stator Input Voltage Rating In Volts:** 11.8 **Stator Input Current Rating:** 87.0 milliamperes **Stator Input Electrical Power Rating:** 210.0 milliwatts Frequency In Hertz:

400.0

Zro Resistance In Ohms:

210.00

Zso Resistance In Ohms:

28.00

Zrs Resistance In Ohms:

250.00

Rotor Dc Resistance In Ohms:

143.00

Stator Dc Resistance In Ohms:

24.00

NSN 5990-00-160-1072 Control Transformer Synchro - Page 2 of 2



Phase Shift Angle In Deg:
9.000 input to output
Maximum Total Null Voltage Output In Millivolts Per Volt:
30.00
Actuator Friction Torque At Minus 55 Deg Celsius:
16.0 centimeter-grams
Actuator Friction Torque At Plus 25 Deg Celsius:
4.0 centimeter-grams
Pilot Length:
Between 0.0380 inches and 0.0480 inches
Mounting Surface To Terminal End Distance:
1.2410 inches
Terminal Location:
Rear
Plus J Zro Reactance In Ohms:
690.00
Plus J Zso Reactance In Ohms:
114.00
Plus J Zrs Reactance In Ohms:
73.00
Shaft Type:
Round single shaft
Transformation Ratio:
2.303 rotor to stator
Terminal Type And Quantity:
5 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A07800