

View Online at <https://aerobasegroup.com/nsn/5990-00-187-5249>

Body Material:

Any acceptable

Body Style:

Standard round a

Pilot Diameter:

Between 0.4995 inches and 0.5000 inches

Overall Length:

1.6350 inches

Flange Diameter:

Between 0.7470 inches and 0.7500 inches

Flange Thickness:

0.0620 inches

Undercut Diameter:

Between 0.6880 inches and 0.6910 inches

Undercut Width:

0.0620 inches

Shaft Diameter:

0.0895 inches single shaft and 0.9000 inches single shaft

Shaft Length:

0.3600 inches single shaft and 0.3900 inches single shaft

Body Size:

8

Rotor Input Voltage Rating In Volts:

115.0

Frequency In Hertz:

400.0

Rotor Input Current Rating:

30.0 milliamperes

Rotor Input Electrical Power Rating:

800.0 milliwatts

Zro Resistance In Ohms:

900.00

Zso Resistance In Ohms:

10.00

Zrs Resistance In Ohms:

1500.00

Phase Shift Angle In Deg:

11.000 input to output

Torque Gradient Per Angular Deg:

2400.0 millimeter-milligrams

Pilot Length:

0.0430 inches

Mounting Surface To Terminal End Distance:

1.0815 inches

Terminal Location:

Rear

Plus J Zro Reactance In Ohms:

3850.00

Shaft Slot Depth:

0.0200 inches single shaft

Plus J Zso Reactance In Ohms:

36.00

Shaft Slot Width:

0.0200 inches single shaft

Plus J Zrs Reactance In Ohms:

375.00

Shaft Type:

Round, slotted single shaft

Terminal Type And Quantity:

5 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A07800