

View Online at <https://aerobasegroup.com/nsn/5990-00-195-9460>

Body Material:

Steel, corrosion resisting

Body Style:

Standard round c

Shoulder Diameter:

0.9750 inches

Pilot Diameter:

0.5000 inches

Overall Length:

1.7500 inches

Flange Diameter:

1.0600 inches

Flange Thickness:

0.0900 inches

Undercut Diameter:

0.9990 inches

Undercut Width:

0.0500 inches

Shaft Diameter:

0.0900 inches single shaft

Shaft Length:

0.5000 inches single shaft

Fragility Factor:

Moderately rugged

Body Size:

11

Rotor Input Voltage Rating In Volts:

26.0

Frequency In Hertz:

400.0

Rotor Input Current Rating:

160.0 milliamperes

Rotor Input Electrical Power Rating:

550.0 milliwatts

Zro Resistance In Ohms:

760.00

Zso Resistance In Ohms:

400.00

Zrs Resistance In Ohms:

850.00

Rotor Dc Resistance In Ohms:

400.00

Stator Dc Resistance In Ohms:

300.00

Phase Shift Angle In Deg:

5.200 input to output

Maximum Fundamental Null Voltage In Millivolts Per Volt:

30.00 input

Maximum Total Null Voltage Output In Millivolts Per Volt:

70.00

Electrical Error Angular Range In Minutes:

-7.0/+7.0

Actuator Friction Torque At Minus 55 Deg Celsius:

15.0 centimeter-grams

Actuator Friction Torque At Plus 25 Deg Celsius:

6.0 centimeter-grams

Pilot Length:

0.0620 inches

Shoulder Length:

0.0620 inches

Mounting Surface To Terminal End Distance:

1.3400 inches

Terminal Location:

Rear

Plus J Zro Reactance In Ohms:

4000.00

Shaft Slot Depth:

0.0300 inches single shaft

Plus J Zso Reactance In Ohms:

2360.00

Shaft Slot Width:

0.0200 inches single shaft

Plus J Zrs Reactance In Ohms:

300.00

Shaft Type:

Round single shaft

Transformation Ratio:

0.650 rotor to stator

Terminal Type And Quantity:

5 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A07800