

View Online at <https://aerobasegroup.com/nsn/5990-00-202-5127>

Body Material:

Steel, corrosion resisting

Body Style:

Standard round c

Shoulder Diameter:

Between 0.9995 inches and 1.0000 inches

Pilot Diameter:

Between 0.6245 inches and 0.6250 inches

Overall Length:

1.9750 inches

Flange Diameter:

Between 1.0610 inches and 1.0620 inches

Flange Thickness:

0.0930 inches

Undercut Diameter:

1.9750 inches

Undercut Width:

0.0500 inches

Shaft Diameter:

0.1200 inches rear shaft

Shaft Length:

0.3750 inches both shafts

Body Size:

11

Rotor Input Voltage Rating In Volts:

26.0

Frequency In Hertz:

400.0

Rotor Input Current Rating:

240.0 milliamperes

Rotor Input Electrical Power Rating:

920.0 milliwatts

Zro Resistance In Ohms:

16.00

Zso Resistance In Ohms:

3.70

Zrs Resistance In Ohms:

22.00

Rotor Dc Resistance In Ohms:

8.50

Stator Dc Resistance In Ohms:

3.00

Phase Shift Angle In Deg:

5.000 input to output

Maximum Total Null Voltage Output In Millivolts Per Volt:

20.00

Electrical Error Angular Range In Minutes:

-30.0/+30.0

Pilot Length:

0.0620 inches

Shoulder Length:

0.0620 inches

Mounting Surface To Terminal End Distance:

1.6000 inches

Terminal Location:

Rear

Plus J Zro Reactance In Ohms:

107.00

Shaft Slot Depth:

0.0320 inches single shaft

Plus J Zso Reactance In Ohms:

18.10

Shaft Slot Width:

0.0220 inches single shaft

Plus J Zrs Reactance In Ohms:

8.90

Shaft Type:

Round, slotted single shaft

Transformation Ratio:

0.454 rotor to stator

Terminal Type And Quantity:

5 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A07800