## NSN 5990-00-206-3753

Transmitter Synchro - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5990-00-206-3753

Body Material:
Steel, stainless
Body Style:
Standard round c
Shoulder Diameter:
Between 0.9995 inches and 1.0000 inches
Pilot Diameter:
Between 0.6245 inches and 0.6250 inches
Overall Length:
Between 2.3360 inches and 2.3760 inches
Flange Diameter:
Between 1.0570 inches and 1.0620 inches
Flange Thickness:
0.0930 inches
Undercut Diameter:
0.9750 inches
Undercut Width:
0.0620 inches
Shaft Diameter:
0.1198 inches single shaft and 0.1200 inches single shaft
Shaft Length:
0.5460 inches single shaft and 0.5650 inches single shaft
Fragility Factor:
Moderately rugged
Maximum Tempurature Rise:
20.0 degrees celsius
Securing Hole Quantity:
4
Body Size:
11
Rotor Input Voltage Rating In Volts:
115.0
Frequency In Hertz:
400.0
Rotor Input Current Rating:
31.0 milliamperes
Rotor Input Electrical Power Rating:
490.0 milliwatts

**Zss Resistance In Ohms:** 

**Zro Resistance In Ohms:**Between 3720.00 and 4700.00

Between 410.00 and 500.00

## NSN 5990-00-206-3753

Transmitter Synchro - Page 2 of 3



## **Zro Impedance Magnitude In Ohms:**

Between 80.00 and 84.00

**Zss Impedance Magnitude In Ohms:** 

Between 17.00 and 26.00

Phase Shift Angle In Deg:

4.500 input to output

Maximum Fundamental Null Voltage In Millivolts Per Volt:

45.00 output

Maximum Total Null Voltage Output In Millivolts Per Volt:

75.00

**Electrical Error Angular Range In Minutes:** 

-7.0/+7.0

**Actuator Friction Torque At Minus 55 Deg Celsius:** 

0.07 inch-ounces

**Actuator Friction Torque At Plus 25 Deg Celsius:** 

0.07 inch-ounces

**Pilot Length:** 

Between 0.0450 inches and 0.0650 inches

**Shoulder Length:** 

Between 0.0590 inches and 0.0790 inches

**Mounting Surface To Terminal End Distance:** 

Between 1.7910 inches and 1.8110 inches

**Mounting Facility Screw Thread Series Designator:** 

Unc

**Terminal Location:** 

Rear

**Shaft Slot Depth:** 

0.0250 inches single shaft

**Shaft Slot Width:** 

0.0200 inches single shaft

**Shaft Type:** 

Round, slotted single shaft

**Alignment Hole Depth:** 

0.1250 inches

**Mounting Facility Screw Thread Diameter:** 

0.112 inches

**Transformation Ratio:** 

0.783 rotor to stator

**Alignment Hole Bolt Circle Diameter:** 

0.6250 inches

**Test Data Document:** 

81349-mil-s-20708 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:** 

## NSN 5990-00-206-3753

Transmitter Synchro - Page 3 of 3



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A07800