NSN 5990-00-226-7894

Differential Transmitter Synchro - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5990-00-226-7894

Body Material:

Steel, stainless

Body Style:

Standard round c

Shoulder Diameter:

Between 0.9995 inches and 1.0000 inches

Pilot Diameter:

Between 0.6245 inches and 0.6250 inches

Overall Length:

Between 2.3170 inches and 2.3410 inches

Flange Diameter:

Between 1.0570 inches and 1.0650 inches

Flange Thickness:

Between 0.0900 inches and 0.0960 inches

Undercut Diameter:

Between 0.9700 inches and 0.9800 inches

Undercut Width:

Between 0.0450 inches and 0.0550 inches

Shaft Diameter:

0.1195 inches single shaft and 0.1200 inches single shaft

Shaft Length:

0.5550 inches single shaft and 0.5730 inches single shaft

Maximum Tempurature Rise:

8.0 degrees celsius

Body Size:

11

Stator Input Voltage Rating In Volts:

90.0

Stator Input Current Rating:

60.0 milliamperes

Stator Input Electrical Power Rating:

600.0 milliwatts

Frequency In Hertz:

400.0

Zro Impedance Magnitude In Ohms:

1990.00

Zro Impedance Angle In Deg:

77.30

Zso Impedance Magnitude In Ohms:

1640.00

Zso Impedance Angle In Deg:

80.70

NSN 5990-00-226-7894

Differential Transmitter Synchro - Page 2 of 2



Rotor Dc Resistance In Ohms:
Between 327.25 and 442.75
Stator Dc Resistance In Ohms:
Between 165.75 and 224.25
Phase Shift Angle In Deg:
4.700 input to output
Maximum Fundamental Null Voltage In Millivolts Per Volt:
59.00 output
Maximum Total Null Voltage Output In Millivolts Per Volt:
94.00
Electrical Error Angular Range In Minutes:
-5.0/+5.0
Actuator Friction Torque At Minus 55 Deg Celsius:
16.0 centimeter-grams
Actuator Friction Torque At Plus 25 Deg Celsius:
4.0 centimeter-grams
Pilot Length:
Between 0.0590 inches and 0.0650 inches
Shoulder Length:
Between 0.0590 inches and 0.0650 inches
Mounting Surface To Terminal End Distance:
Between 1.7620 inches and 1.7680 inches
Terminal Location:
Rear
Shaft Slot Depth:
0.0300 inches single shaft
Shaft Slot Width:
0.0250 inches single shaft
Shaft Type:
Round, slotted single shaft
Transformation Ratio:
Between 1.108 rotor to stator and 1.200 rotor to stator
Terminal Type And Quantity:
6 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A07800