Control Transformer Synchro - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5990-00-234-9136

Body Material:
Steel, stainless
Body Style:
Standard round a
Pilot Diameter:
Between 0.4995 inches and 0.5000 inches
Overall Length:
Between 1.6060 inches and 1.6300 inches
Flange Diameter:
Between 0.7490 inches and 0.7500 inches
Flange Thickness:
Between 0.0590 inches and 0.0650 inches
Undercut Diameter:
Between 0.6880 inches and 0.6910 inches
Undercut Width:
Between 0.0590 inches and 0.0650 inches
Shaft Diameter:
0.0895 inches single shaft and 0.0900 inches single shaft
Shaft Length:
0.3660 inches single shaft and 0.3900 inches single shaft
Body Size:
8
Stator Input Voltage Rating In Volts:
26.0
Stator Input Current Rating:
36.0 milliamperes
Stator Input Electrical Power Rating:
0.133 watts
Frequency In Hertz:
400.0
Zro Impedance Magnitude In Ohms:
1480.00
Zro Impedance Angle In Deg:
80.90
Zso Impedance Magnitude In Ohms:
930.00
Zso Impedance Angle In Deg:
79.40
Zrs Impedance Magnitude In Ohms:
317.00
Zrs Impedance Angle In Deg:
31.40

Control Transformer Synchro - Page 2 of 2



Zss Impedance Magnitude In Ohms: 208.00 Zss Impedance Angle In Deg: 30.30 Phase Shift Angle In Deg: 6.500 input to output Maximum Fundamental Null Voltage In Millivolts Per Volt: 20.00 output **Electrical Error Angular Range In Minutes:** -12.8/+12.8 Actuator Friction Torque At Minus 55 Deg Celsius: 9.0 centimeter-grams Actuator Friction Torque At Plus 25 Deg Celsius: 3.0 centimeter-grams **Pilot Length:** 0.0380 mils and 0.0430 centimeters **Mounting Surface To Terminal End Distance:** 1.2400 inches **Terminal Location:** Rear Shaft Slot Depth: 0.0250 inches single shaft and 0.0350 inches single shaft Shaft Slot Width: 0.0200 inches single shaft and 0.0300 inches single shaft Shaft Type: Round, slotted single shaft **Transformation Ratio:** 1.138 rotor to stator **Terminal Type And Quantity:** 4 wire lead Shelf Life: N/a Unit Of Measure: **Demilitarization:** Yes - demil/mli Fiig: A07800