

View Online at <https://aerobasegroup.com/nsn/5990-00-239-3349>

Body Material:

Steel, corrosion resisting

Body Style:

Standard round a

Pilot Diameter:

Between 0.4995 inches and 0.5000 inches

Overall Length:

1.8740 inches

Flange Diameter:

0.7500 inches

Flange Thickness:

0.0620 inches

Undercut Diameter:

0.6870 inches

Undercut Width:

0.0620 inches

Shaft Diameter:

0.0895 inches single shaft and 0.0900 inches single shaft

Shaft Length:

0.6340 inches single shaft

Fragility Factor:

Moderately rugged

Maximum Temperature Rise:

3.0 degrees celsius

Body Size:

8

Stator Input Voltage Rating In Volts:

11.8

Stator Input Current Rating:

37.0 milliamperes

Stator Input Electrical Power Rating:

100.0 milliwatts

Frequency In Hertz:

400.0

Zro Resistance In Ohms:

470.00

Zso Resistance In Ohms:

81.00

Zrs Resistance In Ohms:

590.00

Rotor Dc Resistance In Ohms:

381.00

Stator Dc Resistance In Ohms:

Between 48.00 and 73.00

Phase Shift Angle In Deg:

8.500 input to output

Maximum Total Null Voltage Output In Millivolts Per Volt:

40.00

Electrical Error Angular Range In Minutes:

-15.0/+15.0

Actuator Friction Torque At Minus 55 Deg Celsius:

9.0 centimeter-grams

Actuator Friction Torque At Plus 25 Deg Celsius:

3.0 centimeter-grams

Pilot Length:

0.0620 inches

Mounting Surface To Terminal End Distance:

1.2400 inches

Terminal Location:

Rear

Plus J Zro Reactance In Ohms:

1770.00

Shaft Slot Depth:

0.0300 inches single shaft

Plus J Zso Reactance In Ohms:

330.00

Shaft Slot Width:

0.0250 inches single shaft

Plus J Zrs Reactance In Ohms:

190.00

Shaft Type:

Round, slotted single shaft

Terminal Type And Quantity:

5 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A07800