

View Online at <https://aerobasegroup.com/nsn/5990-00-251-7822>

**Body Material:**

Steel, corrosion resisting

**Body Style:**

Standard round c

**Shoulder Diameter:**

Between 0.9995 inches and 1.0000 inches

**Pilot Diameter:**

Between 0.6245 inches and 0.6250 inches

**Overall Length:**

2.3560 inches

**Flange Diameter:**

Between 1.0570 inches and 1.0620 inches

**Flange Thickness:**

0.0930 inches

**Undercut Diameter:**

0.9750 inches

**Undercut Width:**

0.0620 inches

**Shaft Diameter:**

0.1198 inches single shaft and 0.1200 inches single shaft

**Shaft Length:**

0.5550 inches single shaft

**Fragility Factor:**

Moderately rugged

**Maximum Temperature Rise:**

20.0 degrees celsius

**Body Size:**

11

**Rotor Input Voltage Rating In Volts:**

26.0

**Frequency In Hertz:**

400.0

**Rotor Input Current Rating:**

280.0 milliamperes

**Rotor Input Electrical Power Rating:**

1.0 watts

**Zss Impedance Magnitude In Ohms:**

Between 3.40 and 4.20

**Zss Impedance Angle In Deg:**

Between 17.00 and 24.00

**Phase Shift Angle In Deg:**

6.000 input to output

**Spline Tooth Quantity:**

21 single shaft

**Receiver Error Angular Range In Minutes:**

-60.0/+60.0

**Torque Gradient Per Angular Deg:**

0.008 inch-ounces

**Alignment Hole Quantity:**

4

**Pilot Length:**

0.0620 inches

**Shoulder Length:**

0.0620 inches

**Mounting Surface To Terminal End Distance:**

1.8010 inches

**Spline Tooth Diametral Pitch:**

120 single shaft

**Shaft Thread Series Designator:**

Unf single shaft

**Shaft Thread Direction:**

Right-hand single shaft

**Shaft Thread Class:**

2a single shaft

**Terminal Location:**

Rear

**Shaft Thread Length:**

0.2000 inches single shaft

**Shaft Type:**

Spline w/threads single shaft

**Alignment Hole Depth:**

0.1250 inches

**Transformation Ratio:**

0.454 stator to rotor

**Alignment Hole Bolt Circle Diameter:**

0.8120 inches

**Shaft Thread Size:**

0.190 inches single shaft

**Test Data Document:**

81349-mil-s-20708 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

5 screw

**Specification Data:**

81349-mil-s-20708/5 government specification

**Shelf Life:**

Nil

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A07800