

View Online at <https://aerobasegroup.com/nsn/5990-00-276-8650>

Body Material:

Steel, stainless

Body Style:

Standard round c

Shoulder Diameter:

Between 1.3116 inches and 1.3120 inches

Pilot Diameter:

Between 0.8745 inches and 0.8750 inches

Overall Length:

2.3120 inches

Flange Diameter:

Between 1.4320 inches and 1.4370 inches

Flange Thickness:

0.0930 inches

Undercut Diameter:

1.3120 inches

Undercut Width:

0.0780 inches

Shaft Diameter:

0.1867 inches single shaft and 0.1872 inches single shaft

Shaft Length:

0.5450 inches single shaft and 0.5650 inches single shaft

Fragility Factor:

Moderately rugged

Maximum Temperature Rise:

10.0 degrees celsius

Body Size:

15

Stator Input Voltage Rating In Volts:

90.0

Stator Input Current Rating:

10.0 milliamperes

Stator Input Electrical Power Rating:

140.0 milliwatts

Frequency In Hertz:

400.0

Zso Impedance Magnitude In Ohms:

Between 7800.00 and 9512.00

Zso Impedance Angle In Deg:

Between 77.80 and 84.50

Zrs Impedance Magnitude In Ohms:

Between 1050.00 and 1300.00

Zrs Impedance Angle In Deg:

Between 26.00 and 33.00

Phase Shift Angle In Deg:

5.500 input to output

Maximum Fundamental Null Voltage In Millivolts Per Volt:

32.00 output

Maximum Total Null Voltage Output In Millivolts Per Volt:

60.00

Electrical Error Angular Range In Minutes:

-6.0/+6.0

Torque Gradient Per Angular Deg:

0.050 inch-ounces

Alignment Hole Quantity:

4

Pilot Length:

0.0400 inches

Shoulder Length:

0.1320 inches

Mounting Surface To Terminal End Distance:

1.7720 inches

Terminal Location:

Rear

Shaft Slot Depth:

0.0250 inches single shaft

Shaft Slot Width:

0.0200 inches single shaft

Shaft Type:

Round, slotted single shaft

Alignment Hole Depth:

0.1250 inches

Transformation Ratio:

0.735 rotor to stator

Alignment Hole Bolt Circle Diameter:

1.1000 inches

Test Data Document:

81349-mil-s-20708 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

5 screw

Specification Data:

81349-mil-s-20708/15 government specification

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A07800