NSN 5990-00-332-1735

Differential Transmitter Synchro - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5990-00-332-1735

Body Style:

Standard round b

Shoulder Diameter:

Between 1.0000 inches and 1.0005 inches

Pilot Diameter:

Between 0.6250 inches and 0.6255 inches

Overall Length:

Between 2.4140 inches and 2.4260 inches

Flange Diameter:

Between 1.0570 inches and 1.0650 inches

Flange Thickness:

Between 0.0900 inches and 0.0930 inches

Undercut Width:

0.0500 inches

Shaft Diameter:

0.1195 inches single shaft and 0.1200 inches single shaft

Shaft Length:

0.5620 inches single shaft

Shaft Undercut Width:

0.1710 inches single shaft

Securing Hole Quantity:

4

Body Size:

11

Stator Input Voltage Rating In Volts:

11.8

Stator Input Current Rating:

Between 230.0 milliamperes and 270.0 milliamperes

Stator Input Electrical Power Rating:

800.0 milliwatts

Frequency In Hertz:

400.0

Zro Impedance Magnitude In Ohms:

72.30

Zro Impedance Angle In Deg:

70.00

Zso Impedance Magnitude In Ohms:

35.70

Zso Impedance Angle In Deg:

75.50

Phase Shift Angle In Deg:

8.700 input to output

NSN 5990-00-332-1735 Differential Transmitter Synchro - Page 2 of 2



Electrical Error Angular Range in Minutes:
-7.0/+7.0
Actuator Friction Torque At Minus 55 Deg Celsius:
16.00 centimeter-grams
Actuator Friction Torque At Plus 25 Deg Celsius:
8.00 centimeter-grams
Pilot Length:
Between 0.0590 inches and 0.0650 inches
Shoulder Length:
Between 0.0590 inches and 0.0650 inches
Mounting Surface To Terminal End Distance:
1.8000 inches
Mounting Facility Screw Thread Series Designator:
Unc
Terminal Location:
Rear
Shaft Slot Depth:
0.0300 inches single shaft
Shaft Slot Width:
0.2500 inches single shaft
Shaft Type:
Round, slotted, undercut single shaft
Transformation Ratio:
1.270 rotor to stator
Shaft Tip Length:
0.2660 inches single shaft
Shaft Undercut Diameter:
0.1130 inches single shaft and 0.1170 inches single shaft
Terminal Type And Quantity:
6 screw
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A07800