

View Online at <https://aerobasegroup.com/nsn/5990-00-412-4411>

**Body Material:**

Steel, stainless

**Body Style:**

Standard round a

**Pilot Diameter:**

Between 0.4995 inches and 0.5000 inches

**Overall Length:**

Between 1.7420 inches and 1.7660 inches

**Flange Diameter:**

Between 0.7450 inches and 0.7530 inches

**Flange Thickness:**

0.0620 inches

**Undercut Diameter:**

0.6870 inches

**Undercut Width:**

0.0620 inches

**Shaft Diameter:**

0.1195 inches single shaft and 0.1200 inches single shaft

**Shaft Length:**

0.4610 inches single shaft and 0.4850 inches single shaft

**Maximum Temperature Rise:**

3.0 degrees celsius

**Body Size:**

8

**Rotor Input Voltage Rating In Volts:**

26.0

**Frequency In Hertz:**

400.0

**Rotor Input Current Rating:**

56.0 milliamperes

**Rotor Input Electrical Power Rating:**

47.0 milliwatts

**Zro Impedance Magnitude In Ohms:**

520.00

**Zro Impedance Angle In Deg:**

69.00

**Zso Impedance Magnitude In Ohms:**

665.00

**Zso Impedance Angle In Deg:**

73.50

**Rotor Dc Resistance In Ohms:**

145.00

**Stator Dc Resistance In Ohms:**

145.00

**Phase Shift Angle In Deg:**

18.000 input to output

**Maximum Fundamental Null Voltage In Millivolts Per Volt:**

38.00 output

**Maximum Total Null Voltage Output In Millivolts Per Volt:**

60.00

**Electrical Error Angular Range In Minutes:**

-10.0/+10.0

**Actuator Friction Torque At Minus 55 Deg Celsius:**

16.0 centimeter-grams

**Actuator Friction Torque At Plus 25 Deg Celsius:**

4.0 centimeter-grams

**Pilot Length:**

0.0400 inches

**Mounting Surface To Terminal End Distance:**

1.2810 inches

**Terminal Location:**

Rear

**Shaft Slot Depth:**

0.0300 inches single shaft

**Shaft Slot Width:**

0.0250 inches single shaft

**Shaft Type:**

Round, slotted single shaft

**Transformation Ratio:**

1.000 rotor to stator

**Terminal Type And Quantity:**

7 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A07800