

View Online at <https://aerobasegroup.com/nsn/5990-00-421-0953>

Body Material:

Steel, stainless

Body Style:

Standard round c

Shoulder Diameter:

Between 0.9995 inches and 1.0000 inches

Pilot Diameter:

Between 0.6245 inches and 0.6250 inches

Overall Length:

Between 2.4110 inches and 2.4150 inches

Flange Diameter:

Between 1.0570 inches and 1.0650 inches

Flange Thickness:

0.0930 inches

Undercut Diameter:

0.9750 inches

Undercut Width:

0.0500 inches

Shaft Diameter:

0.1870 inches single shaft and 0.1872 inches single shaft

Shaft Length:

0.5550 inches single shaft

Fragility Factor:

Moderately rugged

Body Size:

11

Rotor Input Voltage Rating In Volts:

115.0

Frequency In Hertz:

400.0

Rotor Input Current Rating:

145.0 milliamperes

Rotor Input Electrical Power Rating:

760.0 milliwatts

Zro Impedance Magnitude In Ohms:

179.00

Zro Impedance Angle In Deg:

78.00

Rotor Dc Resistance In Ohms:

21.00

Stator Dc Resistance In Ohms:

4.20

Phase Shift Angle In Deg:

7.000 input to output

Maximum Total Null Voltage Output In Millivolts Per Volt:

20.00

Electrical Error Angular Range In Minutes:

-3.0/+3.0

Alignment Hole Quantity:

4

Pilot Length:

0.0620 inches

Shoulder Length:

0.0620 inches

Mounting Surface To Terminal End Distance:

1.7890 inches

Terminal Location:

Rear

Shaft Slot Depth:

0.0210 inches single shaft and 0.0310 inches single shaft

Shaft Slot Width:

0.0200 inches single shaft and 0.0300 inches single shaft

Shaft Type:

Round, slotted single shaft

Alignment Hole Depth:

0.1250 inches

Transformation Ratio:

0.454 rotor to stator

Alignment Hole Bolt Circle Diameter:

0.8120 inches

Terminal Type And Quantity:

7 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A07800