## NSN 5990-00-424-8872

Transmitter Synchro - Page 1 of 2



_	
	View Online at https://aerobasegroup.com/nsn/5990-00-424-88
	Body Material:
	Steel, corrosion resisting
	Body Style:
	Standard round a
	Pilot Diameter:
	Between 0.4995 inches and 0.5000 inches
	Overall Length:
	Between 1.6010 inches and 1.6310 inches
	Flange Diameter:
	0.7530 inches
	Flange Thickness:
	0.0620 inches
	Undercut Diameter:
	Between 0.6880 inches and 0.6910 inches
	Undercut Width:
	0.0620 inches
	Shaft Diameter:
	0.0895 inches single shaft and 0.0900 inches single shaft
	Shaft Length:
	0.3600 inches single shaft and 0.3900 inches single shaft
	Fragility Factor:
	Moderately rugged
	Maximum Tempurature Rise:
	5.0 degrees celsius
	Body Size:
	8
	Rotor Input Voltage Rating In Volts:
	26.0
	Frequency In Hertz:
	400.0
	Rotor Input Electrical Power Rating:
	1.3 watts
	Phase Shift Angle In Deg:
	18.000 input to output
	Maximum Fundamental Null Voltage In Millivolts Per Volt:
	20.00 output
	Maximum Total Null Voltage Output In Millivolts Per Volt:
	30.00
	Electrical Error Angular Range In Minutes:
	-10.0/+10.0
	Dilet Length.

Pilot Length:

0.0430 inches

## **NSN 5990-00-424-8872** Transmitter Synchro - Page 2 of 2



Mounting Surface To Terminal End Distance:	
1.2410 inches	
Terminal Location:	
Rear	
Shaft Slot Depth:	
0.0150 inches single shaft and 0.0300 inches single shaft	
Shaft Slot Width:	
0.0250 inches single shaft	
Shaft Type:	
Round, slotted single shaft	
Transformation Ratio:	
0.423 rotor to stator	
Terminal Type And Quantity:	
6 wire lead	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A07800	