

View Online at <https://aerobasegroup.com/nsn/5990-00-435-1931>

Body Material:

Steel, stainless

Body Style:

Standard round a

Pilot Diameter:

Between 0.4995 inches and 0.5000 inches

Overall Length:

1.6550 inches

Flange Diameter:

Between 0.7470 inches and 0.7500 inches

Flange Thickness:

0.0620 inches

Undercut Diameter:

0.6910 inches

Undercut Width:

0.0620 inches

Shaft Diameter:

0.0895 inches single shaft and 0.0900 inches single shaft

Shaft Length:

0.3750 inches single shaft

Fragility Factor:

Moderately rugged

Body Size:

8

Stator Input Voltage Rating In Volts:

11.8

Stator Input Current Rating:

33.0 milliamperes

Stator Input Electrical Power Rating:

33.0 milliwatts

Frequency In Hertz:

400.0

Zro Resistance In Ohms:

109.00

Zso Resistance In Ohms:

81.00

Zrs Resistance In Ohms:

102.00

Rotor Dc Resistance In Ohms:

Between 70.00 and 88.20

Stator Dc Resistance In Ohms:

Between 57.60 and 70.40

Phase Shift Angle In Deg:

8.500 input to output

Maximum Total Null Voltage Output In Millivolts Per Volt:

30.00

Electrical Error Angular Range In Minutes:

-7.0/+7.0

Actuator Friction Torque At Minus 55 Deg Celsius:

6.00 centimeter-grams

Actuator Friction Torque At Plus 25 Deg Celsius:

3.00 centimeter-grams

Pilot Length:

0.0400 inches

Mounting Surface To Terminal End Distance:

1.2800 inches

Terminal Location:

Rear

Plus J Zro Reactance In Ohms:

362.00

Shaft Slot Depth:

0.0250 inches single shaft

Plus J Zso Reactance In Ohms:

330.00

Shaft Slot Width:

0.0200 inches single shaft

Plus J Zrs Reactance In Ohms:

35.00

Shaft Type:

Round, slotted single shaft

Transformation Ratio:

1.150 rotor to stator

Terminal Type And Quantity:

6 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A07800