

View Online at <https://aerobasegroup.com/nsn/5990-00-458-2959>

Body Material:

Steel, stainless

Body Style:

Standard round a

Pilot Diameter:

Between 0.4995 inches and 0.5000 inches

Overall Length:

1.7840 inches

Flange Diameter:

Between 0.7490 inches and 0.7500 inches

Flange Thickness:

0.0620 inches

Undercut Diameter:

Between 0.6880 inches and 0.6910 inches

Undercut Width:

0.0620 inches

Shaft Diameter:

0.0895 inches single shaft and 0.0900 inches single shaft

Shaft Length:

0.5430 inches single shaft

Body Size:

8

Rotor Input Voltage Rating In Volts:

115.0

Frequency In Hertz:

400.0

Rotor Input Current Rating:

29.0 milliamperes

Rotor Input Electrical Power Rating:

800.0 milliwatts

Zro Resistance In Ohms:

950.00

Zso Resistance In Ohms:

10.00

Zss Resistance In Ohms:

1550.00

Rotor Dc Resistance In Ohms:

700.00

Stator Dc Resistance In Ohms:

10.40

Phase Shift Angle In Deg:

11.000 input to output

Maximum Total Null Voltage Output In Millivolts Per Volt:

75.00

Electrical Error Angular Range In Minutes:

-7.0/+7.0

Actuator Friction Torque At Minus 55 Deg Celsius:

5400.0 millimeter-milligrams

Actuator Friction Torque At Plus 25 Deg Celsius:

2700.0 millimeter-milligrams

Pilot Length:

0.0430 inches

Mounting Surface To Terminal End Distance:

1.3680 inches

Terminal Location:

Rear

Plus J Zro Reactance In Ohms:

3850.00

Shaft Slot Depth:

0.0200 inches single shaft and 0.0300 inches single shaft

Plus J Zso Reactance In Ohms:

36.00

Shaft Slot Width:

0.0150 inches single shaft and 0.0250 inches single shaft

Shaft Type:

Round, slotted single shaft

Plus J Zss Reactance In Ohms:

420.00

Terminal Type And Quantity:

7 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A07800