## NSN 5990-00-458-9643

Transmitter Synchro - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5990-00-458-9643

Body Material:
Steel, stainless
Body Style:
Standard round d
Shoulder Diameter:
Between 2.6950 inches and 2.7000 inches
Pilot Diameter:
0.2900 inches
Second Shoulder Diameter:
2.7500 inches
Second Shoulder Length:
0.3750 inches
Overall Length:
5.1000 inches
Flange Diameter:
Between 3.0980 inches and 3.1000 inches
Flange Thickness:
0.2500 inches
Body Diameter:
2.7000 inches
Shaft Diameter:
0.2403 inches single shaft and 0.2405 inches single shaft
Shaft Length:
0.7300 inches single shaft
Body Size:
32
Rotor Input Voltage Rating In Volts:
115.0
Frequency In Hertz:
400.0
Rotor Input Current Rating:
420.0 milliamperes
Rotor Input Electrical Power Rating:
5.5 watts
Maximum Fundamental Null Voltage In Millivolts Per Volt:
20.00 output
Maximum Total Null Voltage Output In Millivolts Per Volt:
75.00
Electrical Error Angular Range In Minutes:
-10.0/+10.0
Spline Tooth Quantity:
22 single shaft

## NSN 5990-00-458-9643

Transmitter Synchro - Page 2 of 2



**Torque Gradient Per Angular Deg:** 0.400 inch-ounces **Pilot Length:** 0.0300 inches Shoulder Length: 0.6150 inches Aft Of First Flange Diameter: 2.7500 inches Mounting Surface To Terminal End Distance: 4.3700 inches **Spline Tooth Diametral Pitch:** 96 single shaft Shaft Thread Series Designator: Unc single shaft **Shaft Thread Direction:** Right-hand single shaft **Shaft Thread Class:** 2a single shaft **Terminal Location:** Rear Shaft Thread Length: 0.3100 inches single shaft Shaft Type: Spline single shaft **Transformation Ratio:** 0.783 rotor to stator Shaft Thread Size: 0.250 inches single shaft **Terminal Type And Quantity:** 5 screw Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A07800