Control Transformer Synchro - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5990-00-462-9111

Body Material:
Steel, stainless
Body Style:
Standard round a
Pilot Diameter:
Between 0.4995 inches and 0.5000 inches
Overall Length:
Between 1.7260 inches and 1.7560 inches
Flange Diameter:
Between 0.7470 inches and 0.7500 inches
Flange Thickness:
0.0620 inches
Undercut Diameter:
Between 0.6880 inches and 0.6910 inches
Undercut Width:
0.0620 inches
Shaft Diameter:
0.0895 inches single shaft and 0.0900 inches single shaft
Shaft Length:
0.4850 inches single shaft and 0.5150 inches single shaft
Body Size:
8
Stator Input Voltage Rating In Volts:
11.8
Stator Input Current Rating:
24.2 milliamperes
Stator Input Electrical Power Rating:
Between 46.0 watts and 70.0 watts
Frequency In Hertz:
400.0
Zro Resistance In Ohms:
Between 796.00 and 1076.00
Zso Resistance In Ohms:
Between 102.00 and 138.00
Zrs Resistance In Ohms:
Between 935.00 and 1265.00
Rotor Dc Resistance In Ohms:
Between 516.00 and 734.00
Stator Dc Resistance In Ohms:
Between 89.00 and 127.00
Phase Shift Angle In Deg:
9.200 input to output



Maximum Fundamental Null Voltage In Millivolts Per Volt: 22.00 output Maximum Total Null Voltage Output In Millivolts Per Volt: 30.00 **Electrical Error Angular Range In Minutes:** -15.0/+15.0 Actuator Friction Torque At Minus 55 Deg Celsius: 16.0 centimeter-grams Actuator Friction Torque At Plus 25 Deg Celsius: 4.0 centimeter-grams **Pilot Length:** 0.0400 inches Mounting Surface To Terminal End Distance: 1.2410 inches **Terminal Location:** Rear **Plus J Zro Reactance In Ohms:** Between 2340.00 and 2860.00 Shaft Slot Depth: 0.0300 inches single shaft Plus J Zso Reactance In Ohms: Between 382.50 and 517.50 Shaft Slot Width: 0.0250 inches single shaft Plus J Zrs Reactance In Ohms: Between 255.00 and 345.00 Shaft Type: Round, slotted single shaft **Terminal Type And Quantity:** 5 wire lead Shelf Life: N/a Unit Of Measure: --**Demilitarization:** Yes - demil/mli Fiig: A07800