

View Online at <https://aerobasegroup.com/nsn/5990-00-462-9112>

Body Material:

Steel, stainless

Body Style:

Standard round a

Pilot Diameter:

Between 0.4995 inches and 0.5000 inches

Overall Length:

Between 1.7260 inches and 1.7560 inches

Flange Diameter:

Between 0.7470 inches and 0.7500 inches

Flange Thickness:

0.0620 inches

Undercut Diameter:

Between 0.6880 inches and 0.6910 inches

Undercut Width:

0.0620 inches

Shaft Diameter:

0.0895 inches single shaft and 0.0900 inches single shaft

Shaft Length:

0.4850 inches single shaft and 0.5150 inches single shaft

Body Size:

8

Stator Input Voltage Rating In Volts:

11.8

Stator Input Current Rating:

30.0 milliamperes

Stator Input Electrical Power Rating:

Between 58.4 milliwatts and 87.6 milliwatts

Frequency In Hertz:

400.0

Zro Resistance In Ohms:

Between 93.00 and 125.00

Zso Resistance In Ohms:

Between 68.00 and 94.00

Zrs Resistance In Ohms:

Between 102.00 and 138.00

Rotor Dc Resistance In Ohms:

Between 83.30 and 112.70

Stator Dc Resistance In Ohms:

Between 54.40 and 73.60

Phase Shift Angle In Deg:

8.500 input to output

Maximum Fundamental Null Voltage In Millivolts Per Volt:

20.00 output

Maximum Total Null Voltage Output In Millivolts Per Volt:

20.00

Electrical Error Angular Range In Minutes:

-5.0/+5.0

Actuator Friction Torque At Minus 55 Deg Celsius:

16.0 centimeter-grams

Actuator Friction Torque At Plus 25 Deg Celsius:

4.0 centimeter-grams

Pilot Length:

0.0400 inches

Mounting Surface To Terminal End Distance:

1.2410 inches

Terminal Location:

Rear

Plus J Zro Reactance In Ohms:

Between 325.00 and 399.00

Shaft Slot Depth:

0.0300 inches single shaft

Plus J Zso Reactance In Ohms:

Between 297.00 and 363.00

Shaft Slot Width:

0.0250 inches single shaft

Plus J Zrs Reactance In Ohms:

Between 34.00 and 46.00

Shaft Type:

Round, slotted single shaft

Terminal Type And Quantity:

5 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A07800