Control Transformer Synchro - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5990-00-481-5603

Body Material:
Steel, stainless
Body Style:
Standard round a
Pilot Diameter:
Between 0.4995 inches and 0.5000 inches
Overall Length:
1.6150 inches
Flange Diameter:
Between 0.7450 inches and 0.7500 inches
Flange Thickness:
0.0620 inches
Undercut Diameter:
Between 0.6880 inches and 0.6910 inches
Undercut Width:
0.0620 inches
Shaft Diameter:
0.0895 inches single shaft and 0.0900 inches single shaft
Shaft Length:
0.3750 inches single shaft
Body Size:
8
Stator Input Voltage Rating In Volts:
11.8
Stator Input Current Rating:
30.0 milliamperes
Stator Input Electrical Power Rating:
60.0 milliwatts
Frequency In Hertz:
400.0
Zro Resistance In Ohms:
446.00
Zso Resistance In Ohms:
79.00
Zrs Resistance In Ohms:
548.00
Maximum Total Null Voltage Output In Millivolts Per Volt:
40.00
Electrical Error Angular Range In Minutes:
-7.0/+7.0
Actuator Friction Torque At Minus 55 Deg Celsius:
6.0 centimeter-grams



Actuator Friction Torque At Plus 25 Deg Celsius: 3.0 centimeter-grams **Pilot Length:** 0.0400 inches Mounting Surface To Terminal End Distance: 1.2400 inches **Terminal Location:** Rear Plus J Zro Reactance In Ohms: 1887.00 Shaft Slot Depth: 0.0260 inches single shaft Plus J Zso Reactance In Ohms: 350.00 Shaft Slot Width: 0.0250 inches single shaft Plus J Zrs Reactance In Ohms: 182.00 Shaft Type: Round, slotted single shaft **Terminal Type And Quantity:** 5 wire lead Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A07800