NSN 5990-00-484-1517

Transmitter Synchro - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5990-00-484-1517

Body Material:
Steel, stainless
Body Style:
Standard round d
Shoulder Diameter:
Between 1.9850 inches and 1.9900 inches
Pilot Diameter:
0.5950 inches
Second Shoulder Diameter:
Between 1.9985 inches and 1.9995 inches
Second Shoulder Length:
0.1700 inches
Overall Length:
4.5490 inches
Flange Diameter:
Between 2.2490 inches and 2.2500 inches
Flange Thickness:
0.2500 inches
Body Diameter:
1.9900 inches
Shaft Diameter:
0.2380 inches single shaft and 0.2405 inches single shaft
Shaft Length:
0.7090 inches single shaft and 0.7290 inches single shaft
Fragility Factor:
Moderately rugged
Maximum Tempurature Rise:
25.0 degrees celsius
Body Size:
23
Rotor Input Voltage Rating In Volts:
90.0
Frequency In Hertz:
400.0
Rotor Input Current Rating:
866.0 milliamperes
Rotor Input Electrical Power Rating:
7.0 watts
Zso Impedance Magnitude In Ohms:
Between 90.00 and 112.00
Zso Impedance Angle In Deg:

84.00

NSN 5990-00-484-1517

Transmitter Synchro - Page 2 of 3



Zrs Impedance Magnitude In Ohms:
Between 11.00 and 15.00
Zrs Impedance Angle In Deg:
Between 47.00 and 53.00
Phase Shift Angle In Deg:
2.000 input to output
Electrical Error Angular Range In Minutes:
-8.0/+8.0
Actuator Friction Torque At Plus 25 Deg Celsius:
0.20 inch-ounces
Torque Gradient Per Angular Deg:
0.160 inch-ounces
Pilot Length:
0.0430 inches
Shoulder Length:
0.2500 inches
Aft Of First Flange Diameter:
Between 1.9985 inches and 1.9995 inches
Mounting Surface To Terminal End Distance:
3.4100 inches
Shaft Thread Series Designator:
Unf single shaft
Shaft Thread Direction:
Right-hand single shaft
Shaft Thread Class:
2a single shaft
Terminal Location:
Rear
Shaft Thread Length:
0.4450 inches single shaft
Shaft Type:
Round, threaded single shaft
Transformation Ratio:
1.154 rotor to stator
Shaft Thread Size:
0.240 inches single shaft
Terminal Type And Quantity:
6 screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

NSN 5990-00-484-1517

Transmitter Synchro - Page 3 of 3



Fiig:

A07800