

View Online at <https://aerobasegroup.com/nsn/5990-00-503-2895>

Body Material:

Steel, corrosion resisting

Body Style:

Standard round c

Shoulder Diameter:

Between 0.9995 inches and 1.0000 inches

Pilot Diameter:

Between 0.1195 inches and 0.1200 inches

Overall Length:

2.0150 inches

Flange Diameter:

Between 1.0610 inches and 1.0620 inches

Flange Thickness:

0.0620 inches

Undercut Diameter:

0.9750 inches

Undercut Width:

0.0810 inches

Shaft Diameter:

0.1195 inches single shaft and 0.1200 inches single shaft

Shaft Length:

0.3750 inches single shaft

Body Size:

11

Stator Input Voltage Rating In Volts:

22.0

Stator Input Current Rating:

15.0 milliamperes

Stator Input Electrical Power Rating:

74.0 milliwatts

Rotor Input Voltage Rating In Volts:

26.0

Frequency In Hertz:

400.0

Rotor Input Current Rating:

15.0 milliamperes

Rotor Input Electrical Power Rating:

140.0 milliwatts

Zro Resistance In Ohms:

610.00

Zso Resistance In Ohms:

325.00

Zrs Resistance In Ohms:

580.00

Rotor Dc Resistance In Ohms:

400.00

Stator Dc Resistance In Ohms:

140.00

Phase Shift Angle In Deg:

5.000 input to output

Maximum Total Null Voltage Output In Millivolts Per Volt:

30.00

Interaxis Error Angular Range In Minutes:

-12.0/+12.0

Actuator Friction Torque At Minus 55 Deg Celsius:

6.0 centimeter-grams

Actuator Friction Torque At Plus 25 Deg Celsius:

3.0 centimeter-grams

Pilot Length:

0.0620 inches

Shoulder Length:

0.0620 inches

Mounting Surface To Terminal End Distance:

1.6400 inches

Terminal Location:

Rear

Plus J Zro Reactance In Ohms:

1690.00

Shaft Slot Depth:

0.0320 inches single shaft

Plus J Zso Reactance In Ohms:

1460.00

Shaft Slot Width:

0.0220 inches single shaft

Plus J Zrs Reactance In Ohms:

135.00

Shaft Type:

Round, slotted single shaft

Terminal Type And Quantity:

7 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A07800