

View Online at <https://aerobasegroup.com/nsn/5990-00-504-8277>

Body Material:

Steel, corrosion resisting

Body Style:

Standard round b

Shoulder Diameter:

Between 0.9995 inches and 1.0000 inches

Pilot Diameter:

Between 0.4995 inches and 0.5000 inches

Overall Length:

2.1210 inches

Flange Diameter:

Between 1.0570 inches and 1.0620 inches

Flange Thickness:

0.0620 inches

Undercut Width:

0.0620 inches

Shaft Diameter:

0.1200 inches single shaft

Shaft Length:

0.3820 inches single shaft

Fragility Factor:

Moderately rugged

Maximum Temperature Rise:

5.0 degrees celsius

Body Size:

11

Rotor Input Voltage Rating In Volts:

26.0

Frequency In Hertz:

400.0

Rotor Input Current Rating:

93.3 milliamperes

Rotor Input Electrical Power Rating:

490.0 milliwatts

Zro Impedance Magnitude In Ohms:

279.00

Zro Impedance Angle In Deg:

78.50

Zso Impedance Magnitude In Ohms:

50.00

Zso Impedance Angle In Deg:

76.00

Rotor Dc Resistance In Ohms:

28.50

Stator Dc Resistance In Ohms:

11.00

Phase Shift Angle In Deg:

2.000 input to output

Receiver Error Angular Range In Minutes:

-15.0/+15.0

Actuator Friction Torque At Minus 55 Deg Celsius:

15.0 centimeter-grams

Actuator Friction Torque At Plus 25 Deg Celsius:

4.0 centimeter-grams

Pilot Length:

0.0620 inches

Shoulder Length:

0.0620 inches

Mounting Surface To Terminal End Distance:

1.7390 inches

Terminal Location:

Rear

Shaft Slot Depth:

0.0300 inches single shaft

Shaft Slot Width:

0.0250 inches single shaft

Shaft Type:

Round, slotted single shaft

Transformation Ratio:

0.454 stator to rotor

Terminal Type And Quantity:

5 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A07800