# NSN 5990-00-504-8279

Receiver Synchro - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5990-00-504-8279

## Body Material:

Steel, corrosion resisting

#### Body Style:

Standard round double flange b

## Shoulder Diameter:

3.3750 inches

#### **Pilot Diameter:**

1.6300 inches

#### **Overall Length:**

6.3600 inches

#### Flange Diameter:

Between 3.6230 inches and 3.6250 inches

#### Flange Thickness:

Between 0.2450 inches and 0.2500 inches

#### Shaft Diameter:

0.2498 inches single shaft and 0.2500 inches single shaft

#### Shaft Length:

0.7600 inches single shaft and 0.7800 inches single shaft

#### **Fragility Factor:**

Moderately rugged

### **Distance Between Flanges:**

Between 1.8070 inches and 1.8170 inches

#### Maximum Tempurature Rise:

50.0 degrees celsius

### Body Size:

5

#### Rotor Input Voltage Rating In Volts:

115.0

#### Frequency In Hertz:

60.0

# **Rotor Input Current Rating:**

600.0 milliamperes

# Rotor Input Electrical Power Rating:

7.0 watts microwatts

# Torque Gradient Per Angular Deg:

0.400 inch-ounces

# Shaft End Play:

0.0081 inches

# Pilot Length:

0.1750 inches

## Shoulder Length:

1.2450 mils and 1.2550 centimeters

# NSN 5990-00-504-8279

Receiver Synchro - Page 2 of 2



## Shaft Thread Series Designator:

Unf single shaft

## Shaft Thread Direction:

Right-hand single shaft

## Shaft Thread Class:

2a single shaft

# **Terminal Location:**

Rear

# Shaft Thread Length:

0.1770 inches single shaft and 0.1970 inches single shaft

## Shaft Type:

Round, threaded single shaft

# Shaft Thread Size:

0.250 inches single shaft

# **Special Features:**

Round, threaded shaft with slot; slot depth 0.050 inch; slot width 0.030 inch

# Test Data Document:

81349-mil-s-2335 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# Terminal Type And Quantity:

5 screw

#### **Specification Data:**

81349-mil-s-2335 government specification

## Shelf Life:

N/a

#### Unit Of Measure:

---

## Demilitarization:

Yes - demil/mli

## Fiig:

A07800