

View Online at <https://aerobasegroup.com/nsn/5990-00-518-0673>

Body Material:

Steel, corrosion resisting

Body Style:

Standard round c

Shoulder Diameter:

Between 0.9995 inches and 1.0000 inches

Pilot Diameter:

Between 0.6245 inches and 0.6250 inches

Overall Length:

Between 2.2550 inches and 2.2790 inches

Flange Diameter:

Between 1.0570 inches and 1.0650 inches

Flange Thickness:

0.0930 inches

Undercut Diameter:

0.9750 inches

Undercut Width:

0.0500 inches

Shaft Diameter:

0.1195 inches single shaft and 0.1200 inches single shaft

Shaft Length:

0.4900 inches single shaft and 0.5140 inches single shaft

Body Size:

11

Rotor Input Voltage Rating In Volts:

115.0

Frequency In Hertz:

400.0

Rotor Input Current Rating:

50.0 milliamperes

Rotor Input Electrical Power Rating:

970.0 milliwatts

Zro Impedance Magnitude In Ohms:

2598.00

Zro Impedance Angle In Deg:

81.80

Zso Impedance Magnitude In Ohms:

60.00

Zso Impedance Angle In Deg:

78.50

Rotor Dc Resistance In Ohms:

218.00

Stator Dc Resistance In Ohms:

10.50

Phase Shift Angle In Deg:

5.000 input to output

Maximum Fundamental Null Voltage In Millivolts Per Volt:

26.00 output

Maximum Total Null Voltage Output In Millivolts Per Volt:

42.00

Electrical Error Angular Range In Minutes:

-10.0/+10.0

Actuator Friction Torque At Plus 25 Deg Celsius:

4.00 centimeter-grams

Pilot Length:

0.0620 inches

Shoulder Length:

0.0620 inches

Mounting Surface To Terminal End Distance:

1.7650 inches

Shaft Slot Depth:

0.0300 inches single shaft

Shaft Slot Width:

0.0250 inches single shaft

Shaft Type:

Round, slotted single shaft

Transformation Ratio:

0.158 rotor to stator

Terminal Type And Quantity:

5 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A07800