

View Online at <https://aerobasegroup.com/nsn/5990-00-519-9242>

Body Material:

Steel, corrosion resisting

Body Style:

Standard round c

Shoulder Diameter:

Between 1.3115 inches and 1.3120 inches

Pilot Diameter:

Between 0.4995 inches and 0.5000 inches

Overall Length:

2.1310 inches

Flange Diameter:

Between 1.4360 inches and 1.4370 inches

Flange Thickness:

0.0930 inches

Undercut Diameter:

0.3120 inches

Undercut Width:

0.0780 inches

Shaft Diameter:

0.1195 inches single shaft and 0.1200 inches single shaft

Shaft Length:

0.5400 inches single shaft

Maximum Temperature Rise:

6.0 degrees celsius

Body Size:

15

Rotor Input Voltage Rating In Volts:

26.0

Frequency In Hertz:

400.0

Rotor Input Current Rating:

65.0 milliamperes

Rotor Input Electrical Power Rating:

30.0 milliwatts

Zro Resistance In Ohms:

95.00

Zso Resistance In Ohms:

18.30

Zrs Resistance In Ohms:

100.00

Rotor Dc Resistance In Ohms:

40.00

Stator Dc Resistance In Ohms:

10.00

Phase Shift Angle In Deg:

5.500 input to output

Electrical Error Angular Range In Minutes:

-10.0/+10.0

Actuator Friction Torque At Minus 55 Deg Celsius:

15.00 centimeter-grams

Actuator Friction Torque At Plus 25 Deg Celsius:

3.00 centimeter-grams

Alignment Hole Quantity:

4

Pilot Length:

0.0400 inches

Shoulder Length:

0.1320 inches

Mounting Surface To Terminal End Distance:

1.5910 inches

Terminal Location:

Rear

Plus J Zro Reactance In Ohms:

430.00

Shaft Slot Depth:

0.0310 inches single shaft

Plus J Zso Reactance In Ohms:

85.00

Shaft Slot Width:

0.0310 inches single shaft

Plus J Zrs Reactance In Ohms:

62.00

Shaft Type:

Round, slotted single shaft

Alignment Hole Depth:

0.1250 inches

Alignment Hole Bolt Circle Diameter:

0.8750 inches

Terminal Type And Quantity:

5 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A07800