

View Online at <https://aerobasegroup.com/nsn/5990-00-539-7080>

Body Material:

Aluminum

Body Style:

Standard round c

Shoulder Diameter:

Between 1.3115 inches and 1.3120 inches

Pilot Diameter:

Between 0.4995 inches and 0.5000 inches

Overall Length:

1.8810 inches

Flange Diameter:

Between 1.4360 inches and 1.4370 inches

Flange Thickness:

0.0930 inches

Undercut Diameter:

1.3120 inches

Undercut Width:

0.0780 inches

Shaft Diameter:

0.1195 inches single shaft and 0.1200 inches single shaft

Shaft Length:

0.2900 inches single shaft

Fragility Factor:

Moderately rugged

Body Size:

15

Rotor Input Voltage Rating In Volts:

26.0

Frequency In Hertz:

400.0

Rotor Input Current Rating:

100.0 milliamperes

Rotor Input Electrical Power Rating:

450.0 milliwatts

Zro Resistance In Ohms:

45.00

Rotor Dc Resistance In Ohms:

16.00

Stator Dc Resistance In Ohms:

6.70

Electrical Error Angular Range In Minutes:

-40.0/+40.0

Actuator Friction Torque At Minus 55 Deg Celsius:

4.0 centimeter-grams

Actuator Friction Torque At Plus 25 Deg Celsius:

2.0 centimeter-grams

Torque Gradient Per Angular Deg:

2250.0 millimeter-milligrams

Alignment Hole Quantity:

4

Pilot Length:

0.0400 inches

Shoulder Length:

0.1320 inches

Mounting Surface To Terminal End Distance:

1.5910 inches

Terminal Location:

Rear

Plus J Zro Reactance In Ohms:

255.00

Shaft Slot Depth:

0.0210 inches single shaft and 0.0310 inches single shaft

Shaft Slot Width:

0.0210 inches single shaft and 0.0310 inches single shaft

Shaft Type:

Round, slotted single shaft

Alignment Hole Depth:

0.1250 inches

Transformation Ratio:

Between 1.000 rotor to stator and 2.200 rotor to stator

Alignment Hole Bolt Circle Diameter:

0.5000 inches

Terminal Type And Quantity:

5 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A07800