

View Online at <https://aerobasegroup.com/nsn/5990-00-548-6161>

**Body Material:**

Aluminum

**Body Style:**

Standard round c

**Shoulder Diameter:**

Between 0.9995 inches and 1.0000 inches

**Pilot Diameter:**

Between 0.4995 inches and 0.5000 inches

**Overall Length:**

2.1830 inches

**Flange Diameter:**

Between 1.0570 inches and 1.0620 inches

**Flange Thickness:**

0.0620 inches

**Undercut Diameter:**

0.9620 inches

**Undercut Width:**

0.0620 inches

**Shaft Diameter:**

0.1195 inches single shaft and 0.1200 inches single shaft

**Shaft Length:**

0.3820 inches single shaft

**Fragility Factor:**

Moderately rugged

**Maximum Temperature Rise:**

5.0 degrees celsius

**Body Size:**

11

**Rotor Input Voltage Rating In Volts:**

26.0

**Frequency In Hertz:**

400.0

**Rotor Input Current Rating:**

92.0 milliamperes

**Rotor Input Electrical Power Rating:**

500.0 milliwatts

**Zro Impedance Angle In Deg:**

79.00

**Zso Impedance Magnitude In Ohms:**

53.00

**Zso Impedance Angle In Deg:**

76.00

**Rotor Dc Resistance In Ohms:**

28.50

**Stator Dc Resistance In Ohms:**

11.00

**Phase Shift Angle In Deg:**

6.500 input to output

**Maximum Total Null Voltage Output In Millivolts Per Volt:**

35.00

**Electrical Error Angular Range In Minutes:**

-10.0/+10.0

**Actuator Friction Torque At Minus 55 Deg Celsius:**

15.0 centimeter-grams

**Actuator Friction Torque At Plus 25 Deg Celsius:**

4.0 centimeter-grams

**Pilot Length:**

0.0620 inches

**Shoulder Length:**

0.0620 inches

**Mounting Surface To Terminal End Distance:**

1.8010 inches

**Terminal Location:**

Rear

**Shaft Slot Depth:**

0.0300 inches single shaft

**Shaft Slot Width:**

0.0250 inches single shaft

**Shaft Type:**

Round, slotted single shaft

**Transformation Ratio:**

0.454 rotor to stator

**Terminal Type And Quantity:**

5 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A07800